



Safety Containers

## Type II AccuFlow™ Cans FOR FLAMMABLES

*Type II AccuFlow™ Cans combine safety with maximum convenience when handling flammables.*

### Compliant Type II AccuFlow™ Safety Cans

offer additional convenience with two openings; top opening with ergonomically designed lift lever for easy filling, and a second opening equipped with a flexible metal hose for targeted pouring into small apertures. The hose also provides a safe bonding path to the receiving vessel. Patented, innovative manifold automatically vents to provide fast, precision, plug-free pouring. Protection features include a long lasting, stainless steel flame arrester which reliably dissipates heat to prevent flashback ignition and a gasketed, self-closing leak tight lid that automatically vents between 3 and 5 psig (0.2 and 0.35 bar) to guard against pressure buildup at elevated temperatures. Warning label with extra large ID zone permits user to identify contents, department location, or individual user name.

Heavy-duty, lead-free coated steel with reinforcing ribs and tough powder paint finish offers exceptional on-the-job durability. Justrite's quality is backed by an exclusive Ten-Year Warranty. All cans meet OSHA and NFPA, are FM approved, UL/ULC listed, TÜV certified, and accepted under CARB.



7225130

7220120

7210120

7250130



### Leading the Advancement of Safety

#### THE WORLD'S MOST WIDELY TRUSTED SAFETY CAN

Justrite Safety Cans help prevent unthinkable disasters everyday... and even in the face of disaster they continue to protect rescue personnel who use them. That's why Justrite donated 800 safety cans that were used in New York during the rescue efforts following September 11, 2001.

### Type II AccuFlow™ Red Safety Cans for Flammables

Description and Capacity	Hose Dimensions Outer Dia. x L (mm)	Can Dimensions Outer Dia. x H (mm)	Approv./Lstg. Regulation*	Model No.
1 gallon (4L) Steel Safety Can w/Hose	5/8" x 9" (16 x 229)	9 1/2" x 10 1/2" (241 x 267)	FM,UL/ULC,TÜV	7210120
2 gallon (7.5L) Steel Safety Can w/Hose	5/8" x 9" (16 x 229)	9 1/2" x 13 1/4" (241 x 337)	FM,UL/ULC,TÜV	7220120
2 1/2 gallon (9.5L) Steel Safety Can w/Hose	5/8" x 9" (16 x 229)	11 3/4" x 12" (298 x 305)	FM,UL/ULC,TÜV	7225120
2 1/2 gallon (9.5L) Steel Safety Can w/Hose	1" x 9" (25 x 229)	11 3/4" x 12" (298 x 305)	FM,UL/ULC,TÜV	7225130
5 gallon (19L) Steel Safety Can w/Hose	5/8" x 9" (16 x 229)	11 3/4" x 17 1/2" (298 x 445)	FM,UL/ULC,TÜV	7250120
5 gallon (19L) Steel Safety Can w/Hose	1" x 9" (25 x 229)	11 3/4" x 17 1/2" (298 x 445)	FM,UL/ULC,TÜV	7250130

\*See page 8 for Regulation Key.