

# Straight Blade Receptacles Power Outlet Receptacles & Plugs

20, 30, 50, & 60A

**Pass & Seymour**



Straight Blade Receptacles

Power Outlet Receptacles & Plugs

Rating A. V.	Receptacle/Plug Configuration & NEMA No.	Flush Receptacle	Wall Plate	Surface Receptacle	Plug	Angle Plug	Connector	Catalog Nos.				
30 125	5-30							<b>3802</b> § AL/CU	1-Gang: <b>TP724</b> ** 2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>D0531</b> .57"-1.26"	<b>D0533</b> .57"-1.26"	
30 125	NEMA TT30							<b>3830</b> AL/CU*	1-Gang: <b>TP724</b> ** 2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †			
30 250	6-30							<b>3801</b> AL/CU	1-Gang: <b>TP724</b> ** 2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>D0631</b> .57"-1.26"	<b>3869</b> <b>D0633</b> .57"-1.26"	
50 125	5-50									<b>D0551</b> .57"-1.26"	<b>D0553</b> .57"-1.26"	
50 250	6-50							<b>3804</b> § AL/CU	1-Gang: <b>TP724</b> ** 2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>3852</b> # AL/CU	<b>D0651</b> .57"-1.26"	<b>3869</b> <b>D0653</b> .57"-1.26"
30 125/250 <b>Dryer</b>	10-30							<b>3860</b> AL/CU	1-Gang: <b>TP724</b> ** 2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>388</b> AL/CU	<b>1031</b> <b>3861</b>	
50 125/250 <b>Range</b>	10-50							<b>3890</b> § AL/CU	1-Gang: <b>TP724</b> ** 2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>385</b> AL/CU	<b>1051</b> .57"-1.26"	<b>3861</b> <b>1053</b> .32"-.91"
20 125/250	14-20							<b>3820</b>	1-Gang: <b>SS7</b> **			
30 125/250 <b>Dryer</b>	14-30							<b>3864</b> AL/CU	2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>3884</b> #/388440† AL/CU	<b>1431</b> .57"-1.26"	<b>5746AN</b> <b>3867</b>
30 3ø, 250	15-30							<b>5740</b> AL/CU	2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †			<b>5741AN</b>
50 125/250 <b>Range</b>	14-50							<b>3894</b> § AL/CU	2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †	<b>3854</b> #/385440† AL/CU	<b>1451</b> .57"-1.26"	<b>5745AN</b> <b>3867</b>
50 3ø, 250	15-50							<b>5750</b> AL/CU	2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †			<b>5751AN</b>
60 3ø, 250	15-60							<b>5760</b> AL/CU	2-Gang: <b>SS702</b> ** 2-Gang: <b>TP703</b> †			<b>5761AN</b>
20 3øY, 120/208	18-20							<b>3822</b>	1-Gang: <b>SS7</b> **		<b>7251DF</b> .35"-1.05"	
60 3øY, 120/208	18-60							<b>3870</b> § AL/CU	2-Gang: <b>SS701</b> †		<b>D1861</b> .57"-1.26"	<b>8302AN</b>

\*For recreational vehicles. \*\*For 2 screw mounting. †For 4 screw mounting. ‡In bulk pack of 40 with plastic snap-in wire clamp.  
§Up to #3 AWG aluminum conductors. #Up to #4 AWG aluminum conductors.  
For further information consult Wall Plate Section S (for Stainless Steel versions of TP724 and TP703, refer to pages S-12 and S-13).

All devices listed on this page conform to NEMA WD-1 and WD-6.