



**Product Number:** 64479

**Order Abbreviation:** M175/U/MED

**General Description:** Compact 175W reduced outer jacket, universal burn metal halide lamp, clear

### Product Information

Abbrev. With Packaging Info.	M175UMED 20/CS 1/SKU
ANSI Code	M57/E
ANSI Code 2	M57/E
Approx. Lumens (initial - horizontal)	14400
Approx. Lumens (initial - vertical)	14400
Approx. Lumens (mean - horizontal)	7000
Approx. Lumens (mean - vertical)	7000
Arc Length (in)	1.02
Arc Length (mm)	26
Average Rated Life - Horizontal (hr)	7500
Average Rated Life - (hr)	7500
Average Rated Life - Vertical (hr)	10000
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Compact Metalarc®
Fixture Requirement	E
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	3.39
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	132.00
Nominal Wattage (W)	175.00
Operating Position	Universal
Warm-up Time (min)	2-4

#### **Footnotes**

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.