

## U1980-O-BL



4 Terminal Ringless Plain Top 9-16 In Barrel Lock With Bracket Provision

## **SPECIFICATIONS**

Brand Name	Milbank
Туре	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.5L x 13W x15.25H
Number of Main Breakers	0
Main Breaker Size	No Main Breaker
Cable Entry	Underground with Side Wireway
Terminal	Lay in

Insulation	Glass Polyester
Mounting	Surface Mount
Material	G90 Galvanized Steel with Powder Coat Finish
Number of Jaws	4 Terminal
Bypass Provision	No Bypass
Number of Meter Positions	1 Position
Equipment Ground	Triplex Ground
Hub/Closing Plate	Plain Top
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number of Receptacles	0
Height	15.25 IN
Length	4.5 IN
Width	13 IN

IMPORTANT NOTICE: Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.