

Data Tables

TABLE 6-6. DIMENSIONS AND SHIPPING CARTON INFORMATION

Description	Dimensions in Inches (mm)			Catalog Number	UPC Code
	Height	Width	Depth		
Metallic/Galvanized Steel Enclosure					
30 A Fused	8.70 (220.9)	5.40 (137.2)	3.15 (80.0)	DPF221RP	782114103210
60 A Fused	8.70 (220.9)	5.40 (137.2)	3.15 (80.0)	DPF222RP	782114103227
60 A Non-Fused	8.70 (220.9)	5.40 (137.2)	3.15 (80.0)	DPU222RP	782114103234
60 A Molded Case Switch	8.60 (218.4)	5.30 (134.6)	3.74 (95.0)	DPB222RP	782114208250
Nonmetallic/Polycarbonate Enclosure					
30 A Fused	8.63 (219.0)	5.00 (127.0)	3.50 (88.9)	AC221RNMP-A2	786676405904
60 A Fused	8.63 (219.0)	5.00 (127.0)	3.50 (88.9)	AC222RNMP-A2	786676405959
60 A Non-Fused	8.63 (219.0)	5.00 (127.0)	3.50 (88.9)	AC222URNMP-A2	786676406086
60 A Molded Case Switch	8.63 (219.0)	5.00 (127.0)	3.50 (88.9)	B60NARNMP-A2	786676030175

TABLE 6-7. MOLDED CASE SWITCH

Main Ampere Rating	Maximum hp Rating		Wire Size Range Cu/Al 60°C or 75°C	Catalog Number	UPC Code
	120 V	240 V			
Galvanized Steel					
60	—	10	#14-3	DPB222RP	782114208250
Non-Metallic					
60	—	10	#14-2	B60NARNMP-A2	786676030175

TABLE 6-8. NON-FUSED PULLOUTS

Main Ampere Rating	Maximum hp Rating		Wire Size Range Cu/Al 60°C or 75°C	Catalog Number	UPC Code
	120 V	240 V			
Galvanized Steel					
60	3	10	#14-3	DPU222RP ①	782114103234
Non-Metallic					
60	3	10	#14-2	AC222URNMP-A2 ①	786676406154

① For replacement pullout head, order part number 96-3258-4.

TABLE 6-9. FUSED PULLOUTS

Main Ampere Rating	Maximum hp Rating		Wire Size Range Cu/Al 60°C or 75°C	Catalog Number	UPC Code
	120 V	240 V			
Galvanized Steel					
30	1-1/2	3	#14-3	DPF221RP ②	782114103210
60	3	10	#14-3	DPF222RP ②	782114103227
Non-Metallic					
30	1-1/2	3	#14-2	AC221RNMP-A2 ②	786676406208
60	3	10	#14-2	AC222RNMP-A2 ②	786676406253

② For replacement pullout head, order part number 96-3258-4.

③ To obtain a Service Entrance Rating, the addition of **GB4NM** (Ground Bar Kit) is required.