

Type
Project
Catalog No.
Lamp/Wattage

# **NLOPAC-R6509** AC Opal LED Series Surface Mounted LED

Source: LED, 15 Watts, 1050 Lumens

#### PRODUCT DESCRIPTION

The AC Opal LED Series LED fixture is designed to surface mount over a standard J-Box The Opal produces even illumination. The low profile dimmable unit is cULus wet listed and produces 1050 lumens at 90+ CRI.

## **FEATURES:**

- · High color rendition: 90+ CRI
- · AC LED (No Driver)
- · Dimmable
- · Available in 2700K, 3000K and 4000K
- · Available in white, bronze and natural metal finishes.
- · Mount on standard 4" junction box.
- · ENERGY STAR listed

#### **SPECIFICATION**

**Housings:** One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

**Mounting:** Suitable for installation on most 4" square, octagon or round electrical junction boxes. Can be used with 4" fire-rated electrical junction boxes.

**Optional Mounting:** Can be mounted on 5" or 6" recessed housing using optional torsion spring kit. (See below)



INCLUDES: NLOPAC-56RECKIT Mounting hardware kit Medium base socket adaptor / Quick Connect Quick Connect Hardwire Pigtail

**Optics:** Nora specified and designed precision molded lens for optimal lumen output and even distribution.

**Finishes:** Available in white, bronze and natural metal finishes.

**Ratings:** IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

## **ELECTRICAL**

 Voltage:
 120VAC

 Lumens:
 1050lm

 Current:
 0.15A

 Wattage:
 15 Watts Max

**Dimming:** 5% with electronic low voltage

dimmer or 10% with 2-wire

dimmer

**Click Here** or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab.

## **LABELS AND LISTINGS**

ENERGY STAR Listed cULus Wet Listed 5 Year / 50,000 Hour Limited Warranty














#### PRODUCT IMAGES AND DIMENSIONS





NLOPAC-R6509 DIAMETER: 7-3/8" DEPTH: 7/8"

## 6" AC Onal Series LFD

o No opai conto LEB		TIOO LLD	
CA	T. NO	COLOR TEMP	FINISH
NL	OPAC-R6509	<b>27A</b> 2700K <b>30A</b> 3000K <b>40A</b> 4000K	W White BZ Bronze N Natural Metal

Example: NLOPAC-R650930AW - 6" AC Opal LED, 3000K White finish

