Specialty Wrenches

Can Wrench

Bell System Type

- Two tools in one: saves space in your pouch.
- One end opens telephone box fasteners, the other end
- tightens nuts on binding-post terminals.
- The 7/16" socket has a black finish and the 3/8" socket has a silver finish.
- Sockets are 1-1/4" (32 mm) deep to fit over long binding posts and are thin-walled for easy access into tight areas.
- Socket ends are color-coded for quick identification of socket sizes

- JULKEL	enus are conor-co			allon of socker	· 3/2C3.
Cat. No.	Description	Length	Handle Dia.	Weight (lbs.)	
68005	3/8" and 7/16" hex nut	7" (178 mm)	1" (25 mm)	.35	AWARNING: NO

Hex-socket design enables using a wrench to obtain extra torque. High-impact, break-resistant handle for long and dependable service. Sockets are heat-treated, alloy steel.

KLEIN TOOLS, INC. U.S.A. Cat. No. 604

68005

3146B

3146

NRHDA

Weight (lbs.)

1.76

IOT insulated. Will NOT protect against electrical shock.

Length

13" (330 mm)

openings siz Silver painte	zed to NEMA hardware specifications. ed finish.
Cat. No.	Description
3146B	Large end has 1-1/16" and 1-3/16" openings. Sm
Lineman's	s Wrenches
Forged from heat-treated	n special bar steel and d for long life.
Each end ha	-

Cat. No.

NRHD

- ed from special bar steel and treated for long life.
- end has two different size openings.

- Hole is provided at larger end for turning-in standard pole steps.
- Wrench is suited for use on heavy three-bolt guy clamps on which clearance is limited.

Large end has 1-1/16" and 1-3/16" openings. Small end has 11/16" and 7/8" openings.

Dark blue painted finish (small end is painted silver on Cat. No. 3146A).

Cat. No.	Description	Length	Weight (lbs.)
3146	For 5/8" hardware. Large end has 29/32" and 1-3/32" openings. Small end has 5/8" and 13/16" openings.	13" (330 mm)	1.85
3146A	For 3/4" hardware. Large end has 1-1/16" and 1-5/16" openings. Small end has 5/8" and 7/8" openings.	13" (330 mm)	1.70

3-in-1 Impact Socket

Description

3-in1 Impact Socket

- Includes 3/4" (also works on 13/16"), 1" and 1-1/8" square sizes.
- Fine tuned ball detent provides improved retention, minimizing
- 7/16" hex guick-change adapter included.
- 13/16" diameter, 6" long hollow shaft allows use on long thread

	Replacement Parts	
led bolts.	NRHDA Replacement Adapter	
drops.		NRHD

Length	Weight (lbs.)	Repla	cement Parts	
7-3/4" (197 mm)	2.0	NRHD	A Impact Socket Adapter	

NEW

Lineman's Ratcheting Wrenches

- Bolt-through design allows bolts to pass through the socket.
- 3/4" and 1" x 1-1/8" combination square socket for most common utility hardware.
- Bright yellow socket for easy visibility.
- Works on most common utility pole hardware, such as lag bolts, "C" clamps and suspension bolts.
- KT155T and KT155HD also offer two popular wrench sizes: 9/16" and 3/4".
- Heavy duty design (KT155HD).

Cat. No.	Description	Length	Weight (lbs.)
KT155HD	Ratcheting Lineman's Wrench - Heavy Duty	12" (305 mm)	2.10
KT151T	Ratcheting Lineman's Wrench	13" (330 mm)	2.12
KT155T	5-in-1 Lineman's Wrench	9-3/8" (238 mm)	1.42

All dimensions are in inches and (millimeters).

AWARNING: Always wear approved eye protection.

AWARNING: Do NOT push or hammer wrench.



AWARNING: NOT insulated. Plastic-dipped or slip-on plastic handles are NOT intended for protection against electrical shock

AWARNING: Do NOT extend handle length.



128