

Thermostat Cable 60° C - CL2

Applications: Wiring of Thermostat Controls, Heating and Air Conditioning Equipment, doorbells, as well as other Low Voltage Applications. Sunlight Resistant except CL2P.

Features: Sequential Footage Markings on Spools. Braided Ripcord.

Code Restrictions: OK for use with all Power-Limited Circuits except those in Risers and Plenums.

Construction: Copper Conductors, Polypropylene Insulation, Polyvinyl-Chloride Jacket.



AWG	#/COND.	PACKAGING	SOL	NOM. O.D.	NOM. CAP. PF/FT	LISTINGS	AVG. WT. PER MFT	PART#
20	2	4 x 500 S or 1 x 500 SB	SOL	.118	17	CL2	11	4701
20	3	4 x 500 S or 1 x 500 SB	SOL	.124	17	CL2	14	4702
20	4	4 x 250 S or 1 x 250 SB	SOL	.136	17	CL2	18	4703
20	5	4 x 250 S or 1 x 250 SB	SOL	.148	17	CL2	20	4704
20	6	4 x 250 S or 1 x 250 SB	SOL	.161	17	CL2	24	4705
20	7	4 x 250 S or 1 x 250 SB	SOL	.161	17	CL2	27	4706
20	8	4 x 250 S or 1 x 250 SB	SOL	.174	17	CL2	31	4707
20	9	4 x 250 S or 1 x 250 SB	SOL	.188	17	CL2	35	4708•
20	10	4 x 250 S or 1 x 250 SB	SOL	.204	17	CL2	39	4709•
18	2	4 x 500 S or 1 x 500 SB	SOL	.136	19	CL2	16	4710
18	3	4 x 500 S or 1 x 500 SB	SOL	.144	19	CL2	21	4711
18	4	4 x 250 S or 1 x 250 SB	SOL	.157	19	CL2	26	4712
18	5	4 x 250 S or 1 x 250 SB	SOL	.172	19	CL2	32	4713
18	6	4 x 250 S or 1 x 250 SB	SOL	.188	19	CL2	38	4714
18	7	4 x 250 S or 1 x 250 SB	SOL	.188	19	CL2	44	4715
18	8	4 x 250 S or 1 x 250 SB	SOL	.204	19	CL2	50	4716
18	9	4 x 250 S or 1 x 250 SB	SOL	.220	19	CL2	55	4717
18	10	4 x 250 S or 1 x 250 SB	SOL	.240	19	CL2	61	4718
18	12	1 x 250 S or 1 x 250 SB	SOL	.248	19	CL2	74	4719

• Consult factory for availability. S=Spools SB=Speedbags MFT=1000 Feet


Thermostat Cable, Plenum Rated - CL2P

Applications: Wiring of Thermostat Controls, Heating and Air Conditioning Equipment, doorbells, as well as other Low Voltage Applications. Sunlight Resistant except CL2P.

Features: Sequential Footage Markings on Spools. Braided Ripcord.

Code Restrictions: OK for use with all Power-Limited Circuits.

Construction: Copper Conductors, Low Smoke PVC, Low Smoke PVC Jacket.



AWG	#/COND.	PACKAGING	SOL	NOM. O.D.	NOM. CAP. PF/FT	LISTINGS	AVG. WT. PER MFT	PART#	
18	2	4 x 500 S	SOL	.136	28	CMP, CL2P, C(UL) FT6	17	4760	
18	3	4 x 500 S	SOL	.144	28	CMP, CL2P, C(UL) FT6	23	4761	
18	4	4 x 250 S	SOL	.157	28	CMP, CL2P, C(UL) FT6	29	4762	
18	5	4 x 250 S	SOL	.172	28	CMP, CL2P, C(UL) FT6	35	4763	
18	6	4 x 250 S	SOL	.188	28	CMP, CL2P, C(UL) FT6	42	4764	
18	7	4 x 250 S	SOL	.188	28	CMP, CL2P, C(UL) FT6	47	4765•	
18	8	4 x 250 S	SOL	.204	28	CMP, CL2P, C(UL) FT6	54	4766	
18	9	4 x 250 S	SOL	.220	28	CMP, CL2P, C(UL) FT6	60	4767•	
18	10	4 x 250 S	SOL	.240	28	CMP, CL2P, C(UL) FT6	67	4768	
18	1	2	1 x 250 S	SOL	.248	28	CMP, CL2P, C(UL) FT6	79	4769•

• Consult factory for availability. S=Spools MFT=1000 Feet