



Product Number: 29500

Order Abbreviation: F96T12/DX

General Description: 75W, 96" MOL, T12 instant start Slimline fluorescent lamp, Daylight Deluxe phosphor, 6500K color temperature, 88 CRI. VIVID Color: High CRI lamps for color critical applications.

Product Information

Abbrev. With Packaging Info.	F96T12DX 15/CS 1/SKU
Actual Length (in)	94.000
Actual Length (mm)	2387.60
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	6500
Diameter (in)	1.593
Diameter (mm)	40.46
Initial Lumens at 25C	4360
Mean Lumens at 35C	3837
Nominal Length (in)	96.000
Nominal Length (mm)	2438.40
Nominal Wattage (W)	75.00



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.
- Mean lumens are measured at 40% of average rated lamp life.
- The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).