



**Product Number:** 64031

**Order Abbreviation:** M175/C/U/ED28

**General Description:** 175W METALARC quartz metal halide lamp, E39 base, ED28 bulb, enclosed fixture rated, universal burn, coated, 3800K

#### Product Information

Abbrev. With Packaging Info.	M175CUED28 6/CS 1/SKU
ANSI Code	M57/E
ANSI Code 2	M57/E
Approx. Lumens (initial - horizontal)	12000
Approx. Lumens (initial - vertical)	14
Approx. Lumens (mean - horizontal)	8
Approx. Lumens (mean - vertical)	8
Average Rated Life - Horizontal (hr)	7500
Average Rated Life - (hr)	7500
Average Rated Life - Vertical (hr)	10000
Base	E39 Mogul
Bulb	ED28
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3800
Diameter (in)	3.504
Diameter (mm)	89
Family Brand Name	Metalarc®
Fixture Requirement	E
Hot Restrike Time (min)	7 - 12
Lamp Finish	Coated
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Voltage (V)	132.00
Nominal Wattage (W)	175.00
Operating Position	Universal
Warm-up Time (min)	2 - 4

#### **Footnotes**

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.