

**A-series  
ZQV 4N/4 RD**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

| Type       | ZQV 4N/4 RD                |
|------------|----------------------------|
| Order No.  | <a href="#">2460800000</a> |
| GTIN (EAN) | 4050118476224              |
| Qty.       | 60 pc(s).                  |

**A-series**  
**ZQV 4N/4 RD**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |          |                 |           |
|------------|----------|-----------------|-----------|
| Width      | 22.1 mm  | Width (inches)  | 0.87 inch |
| Height     | 2.8 mm   | Height (inches) | 0.11 inch |
| Depth      | 27.95 mm | Depth (inches)  | 1.1 inch  |
| Net weight | 2.86 g   |                 |           |

**Temperatures**

|                                  |               |                                  |        |
|----------------------------------|---------------|----------------------------------|--------|
| Storage temperature, max.        | 40 °C         | Storage temperature, min.        | 10 °C  |
| Storage temperature              | 10 °C...40 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C        |                                  |        |

**Material data**

|                           |       |        |     |
|---------------------------|-------|--------|-----|
| Material                  | Wemid | Colour | red |
| UL 94 flammability rating | V-0   |        |     |

**Additional technical data**

|                          |     |                |         |
|--------------------------|-----|----------------|---------|
| Explosion-tested version | Yes | Type of fixing | Plugged |
|--------------------------|-----|----------------|---------|

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 6.0   | EC000489    | eClass 6.2 | 27-14-11-40 |
| eClass 9.0 | 27-14-11-40 | eClass 9.1 | 27-14-11-40 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                                                                       |
|--------------------|-------------------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                              |
| Engineering Data   | <a href="#">STEP</a>                                                                                  |
| User Documentation | <a href="#">2434520000_BED-ANL_ZQV_A_REIHE.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a> |