

## S1156-RL-FIG6



4 Terminal Ringless Small Hub Open 200 Ampere Main Breaker 50 Ampere Auxiliary Breaker

### SPECIFICATIONS

Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	50 Ampere Auxiliary Breaker Installed
Application	Meter Socket With Main
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.844L x 13W x 33H
Number of Main Breakers	2
Main Breaker Size	One 125 Ampere Main Breaker
Cable Entry	Overhead or Underground
Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Material	G90 Galvanized Steel with Powder Coat Finish
Number of Jaws	4 Terminal
Bypass Provision	No Bypass
Number of Meter Positions	1 Position
Equipment Ground	4 Barrel Ground Lug
Hub/Closing Plate	Small Hub Opening
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	Three 6 AWG - 350 kcmil
Number Of Receptacles	0
Height	33 IN
Length	43.874 IN
Width	13 IN