

NT-5012

5" Deep Phenolic (Plastic) Baffle with Ring

FEATURES

Trim: Precision spun 0.040 plastic baffle with deep grooves to reduce aperture glare and ring. Non-reflective painted finishes. Trim may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable) and mount socket on bracket.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

GU24

13W-26W GU24 (NHIC-5G24ATFL)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT IMAGES AND DIMENSIONS



NT-5012B




NT-5012C0



NT-5012N



NT-5012W



5" Deep Phenolic Baffle with Ring

Catalog No. _____

NT-5012B = Deep Black Phenolic Baffle with White Plastic Ring

NT-5012C0 = Deep Black Phenolic Baffle with Copper Metal Ring

NT-5012N = Deep Black Phenolic Baffle with Natural Metal Ring

NT-5012W = Deep White Phenolic Baffle with White Plastic Ring

Compatible Housings

Line Voltage

Catalog No. _____

NHIC-501QAT = 5" IC Air-Tight New Construction / 75W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 75W max

NH-501Q = 5" Non-IC New Construction / 75W max

NHR-504Q = 5" Non-IC Remodel / 75W max

NFBIC-5INCATA = 5" IC Air-Tight Fire Rated New Construction / 75W max

GU24

Catalog No. _____

NHIC-5G24ATFL = 5" IC Air-Tight GU24 New Construction / 13W-26W max

Example: **NT-5012B** = Deep Black Phenolic Baffle with White Plastic Ring