



## Ridgeline® Full Brim ANSI • CSA •

Shell constructed from ABS material // Ratchet suspension is easy to adjust, allowing you to modify the fit while wearing the hat // 4-point ratchet suspension may be converted to 6-point ratchet suspension with optional strap (HP6PTSUS) // Replaceable ratchet suspensions available // Replaceable sweat band—padded fabric and polyurethane foam // Ridgeline Full Brim hard hats pass high temperature [HT] and low temperature [LT] // Custom imprinting available

### Vented Full Brim

#### 4-Point Ratchet Vented | 5 Variations

- HP54110V •• White
- HP54113V •• Slate Gray
- HP54130V •• Yellow
- HP54160V •• Blue
- HP54117V •• Matte Black Graphite

### Hydro Dipped

#### 4-Point Ratchet Hydro Dipped | 9 Variations

- HP54116 •• Matte White Graphite Pattern
- HP54116S •• Shiny White Graphite Pattern
- HP54117 •• Matte Black Graphite Pattern
- HP54117S •• Shiny Black Graphite Pattern
- HP54117V •• Matte Black Graphite Pattern (Vented)
- HP54118 •• Matte Copper Pattern
- HP54119 •• Matte Camo Pattern
- HP54MIX •• HP54116 (3), HP54117 (3), HP54118 (3), and HP54119 (3)
- HP54MIXS •• HP54116S (3) and HP54117S (3)



### Standard Full Brim

#### 4-Point Ratchet | 10 Variations

- HP54110 •• White
- HP54111 •• Black
- HP54113 •• Slate Gray
- HP54120 •• Red
- HP54130 •• Yellow
- HP54131 •• Hi-Vis Lime
- HP54135 •• Green
- HP54141 •• Hi-Vis Orange
- HP54160 •• Blue
- HP54170 •• Hi-Vis Pink



HPR541 — 4-Point Ratchet Replacement Suspension



HP6PTSUS — 6-Point Suspension Strap





## Ridgeline® Full Brim

### Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)  
 Suspension: high density polyethylene (HDPE) & high impact nylon  
 Sweat band: polyester fabric & polyurethane (PU) foam

### General Specifications

Weight: 378 gm  
 Shell thickness: 1.7 - 4 mm  
 Dimensions: 31 cm x 27 cm x 15.2 cm  
 Suspension adjust sizing: 6.5 - 8  
 Suspensions: 4-point suspension may be converted to 6-point suspension with optional strap  
 Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15  
 Types: Type 1  
 Classes: Class E, G, and C (Vented: Class C only)  
 Optional features: hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

### Markings

Types: Type 1 offers protection to the top of the head  
 Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection  
 HV: meets all requirements for high visibility  
 LT: provides protection at low temperatures -22°F  
 HT: provides protection at high temperatures 140°F  
 Date code: indicates month and year when the shell was molded – does not indicate service life



### Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use  
 Never alter or modify the shell or suspension system  
 Inspect the hard hat each time before use and replace if there is ANY sign of damage  
 Replace hard hat after it receives a considerable impact  
 Accessories such as liners have not been tested to the requirement of this standard  
 Clean only with mild soap and lukewarm water  
 Store hard hat in a clean, dry place that is out of direct sunlight  
 Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat  
 Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage