

SHOWA

7005PF

The world's first 100% nitrile disposable glove, this N-DEX® glove provides unmatched dexterity and performance across a range of tactical applications using revolutionary SHOWA technology.

FEATURES

- 100% Nitrile, latex-free
- Powder-free
- Low-modulus formulation
- Rolled cuff
- 4 mil thick, 9.5" long

BENEFITS

- Superior durability and versatile performance
- Protects hands from an array of chemical hazards
- Low-modulus nitrile formulation reduces risk of allergies
- Rolled cuff prevents dirt from entering the glove
- Second-skin feel significantly reduces hand fatigue

INDUSTRY



Aerospace



Agriculture



Automotive



Chemical



DIY



Food



Municipal Services



Pharmaceutical



Utilities

IDEAL APPLICATIONS

- Intricate parts handling
- Light assembly of oil-coated pieces
- Handling plants and vegetables
- Mechanical and engineering
- Chemical spray and treatment
- Coating preparation
- Food packing and handling
- Food Service/Food Prep
- Fruit & vegetable processing
- Grain, mill and starch products
- Pet Food production
- Poultry, meat & seafood processing
- Washing and cleaning
- Public utility
- Life sciences
- Cytostatics
- Biotechnology
- Pharmaceuticals & API



TAA PRODUCTS

MADE IN USA

MATERIAL

- Single use
- Unsupported

COATING

- Nitrile

GRIP

- Smooth

STANDARDS

Cat. III



2777

EN ISO 374-5:2016



VIRUS

EN ISO 374-1:2016/Type B



KPT



SHOWA
7005PF



PACKAGING

- 20 Dispenser per case
- 100 Gloves per dispenser
- 2000 Gloves per case



COLOUR

- Light Blue



SIZES

- XS
- S
- M
- L
- XL
- XXL



THICKNESS

- 4 mil



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
7005



MATERIAL
Single use
COATING
Nitrile

SHOWA
6110PF



MATERIAL
Single use
COATING
Biodegradable

SHOWA
9700PF



MATERIAL
Single use
COATING
Nitrile

SHOWA
B6005PF



MATERIAL
Single use
COATING
Nitrile

[USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account. Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved