



Abbrev. With Packaging Info.

11.5 INCHES

Product 64490

Number:

Order

M400/U

M400U 6/CS 1/SKU

**Abbreviation:** 

**General** 400W METALARC quartz metal halide lamp, E39 **Description:** base, BT37 bulb, enclosed fixture rated, universal burn, clear, 4000K

Image for reference only

## **Product Information**

Approx. Lumens (initial - horizontal)	32000
Approx. Lumens (initial - vertical)	36000
Approx. Lumens (mean - horizontal)	20500
Approx. Lumens (mean - vertical)	23500
Arc Length (in)	1.77
Arc Length (mm)	45
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	BT37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc®
Fixture Requirement	S
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	135.00

Nominal Wattage (W) 400.00 **Operating Position** Universal Warm-up Time (min) 2-4

## **Footnotes**

- 20,000 average rated life based on 10 hrs/start. 30,000 average rated life based on 120 hrs/start.
  S = When operated within 15 degrees of vertical, this lamp may be operated in an open luminaire provided the installation is not near people or flammable or combustible material, otherwise it must be operated in a suitably enclosed luminaire. See lamp warning.