

# Exceeding Expectations

## Why Use GE LED Lamps?

### COMPLETE



From LFL to HID and everything in between, GE has a full family of LED lamp replacements for almost every lighting need. All designed by GE engineers.

#### How We Do It

#### Outcomes We Drive



Breadth & Depth



One-Stop Shop

### INNOVATIVE



With Plug & Play simplicity and color enhancing technologies, GE engineers design cutting-edge lamps that allow LEDs to go places they have never gone before.



System Expertise



Patented Color Enhancement



Drive Top Line & Bottom Line

### TRUSTED



When it comes to LED lamps that last up to 50,000 hours, quality and reliability really matter. GE has been designing lamps for over 100 years and backs all LEDs with a limited warranty that you can trust.



In-House Testing



Measuring What Matters



Savings With Confidence



# LED replacement Tubes

## Integrated Plastic Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC	UL	#Location Rating	Additional Information
<b>Integrated 4ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)</b>																
T8	G13	18	31550	LED18ET8/4/830	25	48	2450	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	18	93133	LED18ET8/4/835	25	48	2550	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	18	93135	LED18ET8/4/840	25	48	2550	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	18	93140	LED18ET8/4/850	25	48	2650	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	15	62399	LED15ET8/4/830	25	48	2150	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	15	62401	LED15ET8/4/835	25	48	2250	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	15	62402	LED15ET8/4/840	25	48	2250	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	15	62409	LED15ET8/4/850	25	48	2350	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	15	62410	LED15ET8/4/865	25	48	2350	6500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	61218	LED12ET8/4/830	25	48	1750	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	61223	LED12ET8/4/835	25	48	1800	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	61271	LED12ET8/4/840	25	48	1800	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	61327	LED12ET8/4/850	25	48	1900	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	61329	LED12ET8/4/865	25	48	1900	6500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated	
<b>Integrated 3ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	12	31554	LED12ET8/3/830	25	36	1500	3000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	26544	LED12ET8/3/835	25	36	1550	3500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	26625	LED12ET8/3/840	25	36	1550	4000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	12	26627	LED12ET8/3/850	25	36	1650	5000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated	
<b>Integrated 2ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	9	31557	LED9ET8/2/830	25	24	1350	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	9	26635	LED9ET8/2/835	25	24	1350	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	9	26648	LED9ET8/2/840	25	24	1400	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
	G13	9	26676	LED9ET8/2/850	25	24	1400	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated	
<b>Integrated U6 Plastic Tubes</b>																
	G13	13	43120	LED13ET8/U6/830	12	22.5	1800	3000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast	
	G13	13	43125	LED13ET8/U6/835	12	22.5	1850	3500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast	
	G13	13	43129	LED13ET8/U6/840	12	22.5	1900	4000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast	
	G13	13	43130	LED13ET8/U6/850	12	22.5	1900	5000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast	

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "T/P" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

# LED replacement tubes

## Integrated Glass Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC	UL	#Location Rating	Additional Information
<b>Integrated 4 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
T8	G13	18	35767	LED18ET8/G/4/830	20	48	2400	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	18	35768	LED18ET8/G/4/835	20	48	2500	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	18	35769	LED18ET8/G/4/840	20	48	2500	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	18	35772	LED18ET8/G/4/850	20	48	2600	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	18	35773	LED18ET8/G/4/865	20	48	2600	6500K	80+		50,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	15	35790	LED15ET8/G/4/830	20	48	2100	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	15	35791	LED15ET8/G/4/835	20	48	2200	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	15	35793	LED15ET8/G/4/840	20	48	2200	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	15	35797	LED15ET8/G/4/850	20	48	2300	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	15	35798	LED15ET8/G/4/865	20	48	2300	6500K	80+		50,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	12	43284	LED12ET8/G/4/830	20	48	1700	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	12	43288	LED12ET8/G/4/835	20	48	1750	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	12	43291	LED12ET8/G/4/840	20	48	1750	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	12	43293	LED12ET8/G/4/850	20	48	1850	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
<b>Integrated 4ft Value LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
T8	G13	15	35896	LED15ET8/835-V6P	6	48	1750	3500K	80+		36,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	15	35900	LED15ET8/840-V6P	6	48	1750	4000K	80+		36,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	15	35911	LED15ET8/850-V6P	6	48	1800	5000K	80+		36,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	15	35913	LED15ET8/865-V6P	6	48	1800	6500K	80+		36,000	-	Yes	Damp	Instant or PRS	Ballast
<b>Integrated 3ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	11	35783	LED11ET8/G/3/830	20	36	1450	3000K	80+		50,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	11	35784	LED11ET8/G/3/835	20	36	1500	3500K	80+		50,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	11	35788	LED11ET8/G/3/840	20	36	1500	4000K	80+		50,000	-	Yes	Damp	Instant or PRS	Ballast
	G13	11	35789	LED11ET8/G/3/850	20	36	1600	5000K	80+		50,000	-	Yes	Damp	Instant or PRS	Ballast
<b>Integrated 2ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)</b>																
	G13	8	35775	LED8ET8/G/2/830	20	24	1300	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	8	35776	LED8ET8/G/2/835	20	24	1350	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	8	35778	LED8ET8/G/2/840	20	24	1350	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast
	G13	8	35779	LED8ET8/G/2/850	20	24	1400	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS	Ballast

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 \*\* Minimum order quantity = 6

# UL 1993 Environmental Requirements for LED LAMPS  
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

# LED replacement tubes

## Remote Plastic Tubes - Type C

Remote Plastic 4 ft LED Tubes (Operates on Remote Driver)														
T8	G13	18	TBD	LED21T8/4/830	10	48	2600	3000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94381	LED21T8/4/835	10	48	2650	3500K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94382	LED21T8/4/840	10	48	2750	4000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94383	LED21T8/4/850	10	48	2850	5000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	26059	LED21T8/4/865	10	48	2750	6500K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38954	LED15T8/4/830	10	48	1950	3000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38957	LED15T8/4/835	10	48	2000	3500K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38958	LED15T8/4/840	10	48	2050	4000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38962	LED15T8/4/850	10	48	2100	5000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38964	LED15T8/4/865	10	48	2050	6500K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated
Remote Plastic 3 ft LED Tubes (Operates on Remote Driver)														
G13	13	99692	LED13T8/3/830	20	36	1950	3000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	13	99693	LED13T8/3/835	10	36	2000	3500K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	13	99694	LED13T8/3/840	10	36	2050	4000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	13	99695	LED13T8/3/850	10	36	2100	5000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	16	82343	LED18T8/3/835	10	36	1800	3500K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	16	82345	LED18T8/3/840	10	36	1800	4000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	16	82346	LED18T8/3/850	10	36	1800	5000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
Remote Plastic 2 ft LED Tubes (Operates on Remote Driver)														
G13	8	TBD	LED9T8/2/830	20	24	1100	3000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
G13	8	65706	LED9T8/2/835	20	24	1100	3500K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated	
G13	8	65707	LED9T8/2/840	20	24	1150	4000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated	
G13	8	65711	LED9T8/2/850	20	24	1150	5000K	80+	50,000	Yes	Yes	Damp	Requires Driver, NSF Rated	
G13	8	92997	LED9T8/2/865	20	24	1000	5000K	80+	50,000	-	Yes	Damp	Requires Driver, NSF Rated	
Remote Plastic LED U Tubes (Operates on Remote Driver)														
G13	12	28084	LED14T8/U/835	15	22.5	1700	3500K	80+	50,000	Yes	Yes	Damp	Requires Driver	
G13	12	28164	LED14T8/U/840	15	22.5	1700	4000K	80+	50,000	Yes	Yes	Damp	Requires Driver	

### Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR status: ENERGY STAR certified. Lamps without a ★ are not ENERGY STAR certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

# LED replacement lamps

## RemoteGlass Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC	UL	#Location Rating	Additional Information
<b>Remote 4ft LED Glass Tubes (Operates on Remote Driver)</b>																
T8	G13	18	TBD	LED21T8/G/4/830	20	48	2550	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	18	62428	LED21T8/G/4/835	20	48	2600	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	18	62485	LED21T8/G/4/840	20	48	2700	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	18	62487	LED21T8/G/4/850	20	48	2800	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	18	62406	LED21T8/G/4/835HL	20	48	2750	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver	
	G13	18	62407	LED21T8/G/4/840HL	20	48	2800	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver	
	G13	18	62408	LED21T8/G/4/850HL	20	48	2800	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver	
	G13	18	91475	LED21T8/G/4/830US	20	48	2600	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	18	91496	LED21T8/G/4/835US	20	48	2600	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	18	91497	LED21T8/G/4/840US	20	48	2600	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	18	91498	LED21T8/G/4/850US	20	48	2600	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	15	99696	LED15T8/G/4/830US	20	48	1950	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	15	99697	LED15T8/G/4/835US	20	48	2050	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	15	99698	LED15T8/G/4/840US	20	48	2100	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	15	99699	LED15T8/G/4/850US	20	48	2100	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver - Assembled in USA	
	G13	13	38944	LED15T8/G/4/830	20	48	1850	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	13	38945	LED15T8/G/4/835	20	48	1900	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	13	38950	LED15T8/G/4/840	20	48	1950	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	13	38951	LED15T8/G/4/850	20	48	2050	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	13	38952	LED15T8/G/4/865	20	48	1950	6500K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	10	76194	LED12T8/G/4/830	20	48	1550	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	10	76264	LED12T8/G/4/835	20	48	1600	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	10	76265	LED12T8/G/4/840	20	48	1650	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	10	76271	LED12T8/G/4/850	20	48	1650	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	10	76278	LED12T8/G/4/865	20	48	1600	6500K	80+		50,000	-	Yes	Damp	Requires Driver	
<b>Remote 3ft LED Glass Tubes (Operates on Remote Driver)</b>																
	G13	13	99687	LED15T8/G/3/830	20	36	1800	3000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	13	99688	LED15T8/G/3/835	20	36	1850	3500K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	13	99689	LED15T8/G/3/840	20	36	1900	4000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	13	99691	LED15T8/G/3/850	20	36	1900	5000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	16	38257	LED18T8/G/3/830	20	36	1800	3000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	16	38258	LED18T8/G/3/835	20	36	1800	3500K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	16	38260	LED18T8/G/3/840	20	36	1900	4000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	16	38261	LED18T8/G/3/850	20	36	1900	5000K	80+		50,000	-	Yes	Damp	Requires Driver	
<b>Remote 2ft LED Glass Tubes (Operates on Remote Driver)</b>																
	G13	8	38933	LED9T8/G/2/830	20	24	1000	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	8	38935	LED9T8/G/2/835	20	24	1000	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	8	38936	LED9T8/G/2/840	20	24	1100	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	8	38939	LED9T8/G/2/850	20	24	1100	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver	
	G13	8	38943	LED9T8/G/2/865	20	24	1000	6500K	80+		50,000	-	Yes	Damp	Requires Driver	
<b>Remote 8ft LED Glass Tubes (Operates on Remote Driver)</b>																
	Fa8	30	62326	LED36T8/G/8/830	20	96	4200	3000K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA	
	Fa8	30	62327	LED36T8/G/8/835	20	96	4400	3500K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA	
	Fa8	30	62329	LED36T8/G/8/840	20	96	4400	4000K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA	
	Fa8	30	62349	LED36T8/G/8/850	20	96	4400	5000K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA	
<b>Remote Glass U6 Tubes (Operates on Remote Driver)</b>																
	G13	13	43131	LED15T8/G/U6/830	12	22.5	1700	3000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	13	43135	LED15T8/G/U6/835	12	22.5	1800	3500K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	13	43143	LED15T8/G/U6/840	12	22.5	1800	4000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G13	13	43145	LED15T8/G/U6/850	12	22.5	1800	5000K	80+		50,000	-	Yes	Damp	Requires Driver	
<b>Remote 2ft LED Glass T5 Tubes (Operates on Remote Driver)</b>																
T5	G5	13	76150	LED15T5/G/2/830	20	24	1800	3000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	13	76164	LED15T5/G/2/835	20	24	1850	3500K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	13	76129	LED15T5/G/2/840	20	24	1900	4000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	13	76167	LED15T5/G/2/850	20	24	1900	5000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	13	76192	LED15T5/G/2/865	20	24	1900	6500K	80+		50,000	-	Yes	Damp	Requires Driver	
<b>Remote 4ft LED Glass T5 Tube (Operates on Remote Driver)</b>																
	G5	31	91973	LED36T5/G/4/830	20	46	4100	3000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	31	91976	LED36T5/G/4/835	20	46	4200	3500K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	31	91977	LED36T5/G/4/840	20	46	4400	4000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	31	91997	LED36T5/G/4/850	20	46	4500	5000K	80+		50,000	-	Yes	Damp	Requires Driver	
	G5	31	92006	LED36T5/G/4/865	20	46	4500	6500K	80+		50,000	-	Yes	Damp	Requires Driver	

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★\*\* are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)