

Conduit Bodies and Fittings (for use with Schedule 40 and 80 Conduit)

Expansion Fittings

E945 series expansion fittings are designed to compensate for length changes due to temperature variations in exposed conduit runs.

- Exclusive molded-in mid-point indicator on the piston
- Exclusive 2" expansion fitting with an 8" travel distance
- Two-piece molded design with lubricated seals for easier movement for the life of the product
- Ridges on the fitting for easier installation (sizes 2"-6" only)
- Male terminal adapter end design (1/2"-2" NPT Threads, and 2 1/2"-6" NPSC threads)
- Two O-rings to prevent leakage
- Can be installed vertically or horizontally



Coupling end

E23018

UL LISTED

COUPLING END CAT. NO.	MALE TERMINAL ADAPTER END CAT. NO.	SIZE (IN.)	STD. CTN.	TRAVEL LENGTH (IN.)
E945D	E945DX	1/2	20	4
E945E	E945EX	3/4	15	4
E945F	E945FX	1	10	4
E945G	E945GX	1 1/4	5	4
E945H	E945HX	1 1/2	5	4
E945J	E945JX	2	15	8
E945K	E945KX	2 1/2	10	8
E945L	E945LX	3	10	8
E945M	E945MX	3 1/2	5	8
E945N	E945NX	4	5	8
E945P	E945PX	5	1	8
E945R	E945RX	6	1	8

Short Expansion Couplings

Expand to a maximum of 2".

E23018

UL LISTED

CAT. NO.	SIZE (IN.)	STD. CTN.
E955D	1/2	40
E955E	3/4	40
E955F	1	25
E955G	1 1/4	15
E955H	1 1/2	10
E955J	2	6



Standard Couplings

All socket fittings should be attached using Carlton® solvent cement.




Socket type for joining non-metallic conduit.

LR33856

E23018

Except where noted by ►



CAT. NO.	SIZE (IN.)	STD. CTN.	TYPICAL (IN.)		I.D. (IN.)	O.D. (IN.)	TYPICAL (IN.)	
			A	B			C	L
E940D	1/2	150	.852	.836	.728	1 1/64	1 1/16	1 1/2
CE940DR-CTN	1/2	75	.852	.836	.728	1 1/64	1 1/16	1 1/2
E940E	3/4	100	1.064	1.046	.840	1 1/16	3/4	1 1/8
CE940ER-CTN	3/4	45	1.064	1.046	.840	1 1/16	3/4	1 1/8
E940F	1	50	1.330	1.310	1.210	1 1/8	1 1/16	2
CE940F-UPC	1	50	1.330	1.310	1.210	1 1/8	1 1/16	2
E940G	1 1/4	30	1.677	1.655	1.535	1 63/64	1	2 1/8
E940H	1 1/2	25	1.918	1.894	1.755	2 1/16	1 1/8	2 1/8
E940J	2	30	2.393	2.369	2.190	2 47/64	1 1/16	2 1/2
E940K	2 1/2	20	2.890	2.868	2.688	3 3/16	1 33/64	3 3/16
E940L	3	25	3.515	3.492	3.375	3 31/32	1 1/4	3 1/32
E940M	3 1/2	20	4.015	3.992	3.780	4 9/16	1 1/4	3 3/8
E940N	4	15	4.515	4.491	4.265	5 5/32	1 25/32	3 3/4
E940P	5	8	5.593	5.553	5.097	6 1/4	1 1/8	4 1/8
E940R	6	5	6.658	6.614	6.115	7 1/2	23/16	4 1/8

► Canada only

Special Long-Line Couplings (with Conduit Stop)



CAT. NO.	SIZE (IN.)	STD. CTN.	STD. WT. (LBS.)	LENGTH (IN.)
E941H	1 1/2	40	9	3.19
E941J	2	25	8	3.59
E941K	2 1/2	15	8	4.29
E941L	3	15	14	6.44
E941N	4	10	15	6.96
E941PF	5	4	12	9.63
E941RF	6	5	21	11.75

Fabricated Expansion Couplings

E23018



CAT. NO.	SIZE (IN.)	STD. CTN.	TRAVEL LENGTH (IN.)
E945KXL	2 1/2	10	12