



DIMENSIONS IN PARENTHESIS ARE METRIC

RATINGS			
MAX CONTINUOUS VOLTAGE		CONTINUOUS CURRENT	
PHASE-TO-GND	PHASE-TO-PHASE		
15.2 kV	26.3 kV	200 AMPERE RMS	
SHORT-TIME CURRENT RATINGS			
0.17-SECOND DURATION		3.00 SECOND DURATION	
10,000 AMPERE RMS SYMMETRICAL		3500 AMPERE RMS SYMMETRICAL	
INSULATION WITHSTAND VOLTAGES			
BASIC IMPULSE LEVEL (1.2X50 MICROSEC. WAVE)	AC-60 HERTZ (ONE MINUTE)	DC (15 MINUTE)	PARTIAL DISCHARGE VOLTAGE (CEV)
125 kV CREST	40 kV RMS	78 kV	<3PC @ 19 kV



HUBBELL® POWER SYSTEMS

TITLE
INSULATING CAP
200A 25 KV

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.

SIZE	DWG NO.	CAT / PART / ASSY NO.	REV
S	026079-00	9U01BEW500	0

REV DATE 11/17/03

DO NOT SCALE THIS DRAWING	DRN BY JVR	DATE 11/17/03	SHEET 1 OF 1
---------------------------	------------	---------------	--------------