



Search Parameters:

[e-Catalog](#) > [Load Centers](#) > Residential Load Centers

Load Centers, Residential Load Centers

Product #: TLM4020CCU

Short Description: 40 CIR. 200 A CONVERTIBLE L/C

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Single Phase - USA
Input/Output Voltage	120/240V ac
Type	Standard
Interrupting Capacity Rating	65
Amperage	200A
Device Type	Convertible
Enclosure	Indoor Type 1 Enclosure, Combination
UL/CUL Listing	UL
Phase	1 Phase
Socket Type	0
1" Space	40
1/2" Space	40 , 42 , 4 , 24 , 16 , 20 , 32
Feed	Either
Door	Yes
GSA Compliance	Yes
GO Schedule	137D
List Price	\$477



[View Larger](#)

Publications/Resources

[TLM4020CCU](#)

Additional Resources for Single Phase - USA

Ads

[Application and Technical](#)

[Brochures](#)

[Catalogs and Buyers Guides](#)

[Data Sheets](#)

[Drawings-Outline and Dimensional](#)

[Installation and Instruction](#)

[BIM Files](#)

[Buy Log :1-10](#)

- UL Listed (Panelboards No. 67)
- 60°/75°C Conductor Rating
- Suitable for use as service entrance equipment when installed in accordance with the National Electrical Code
- 22kAIC RMS symmetrical, Except Where Noted
- 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down
- For a listing of CSA Listed load centers, visit www.geelectrical.com

