



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Circuit Breakers](#) > [Molded Case Circuit Breakers](#)

Circuit Breakers, Molded Case Circuit Breakers

Product #: SEHA36AT0060

Short Description: SEH 3P 600V 60A

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

| | |
|---------------------------------|---|
| Category | Spectra RMS™ Electronic Trip |
| Product Line | Spectra RMS - Standard |
| Trip Style | Interchangeable |
| Frame Type | SE150 |
| Amperage | 40A , 50A , 60A |
| Poles | 3 |
| System Voltage | 120 Vac , 120/240 Vac , 240 Vac , 277 Vac , 480 Vac , 600 Vac |
| 120 Vac Interrupting Rating | 65 KAIC |
| 120/240 Vac Interrupting Rating | 65 KAIC |
| 240 Vac Interrupting Rating | 65 KAIC |
| 277 Vac Interrupting Rating | 25 KAIC |
| 480 Vac Interrupting Rating | 25 KAIC |
| 600 Vac Interrupting Rating | 18 KAIC |
| Trip Function | LSI |
| Continuous Current Rated | Standard |
| Suitable for Reverse Feed | Yes |
| Lugs | TCAL18 |
| Long Time | Fixed |
| Short Time | Adjustable |
| Instantaneous | Adjustable |
| Current Metering | No |
| Protective Relays | No |
| Special Markings | HACR , HID |
| UL File # | E11592 |
| CSA File# | LR40350 |
| GSA Compliance | No |
| GO Schedule | 135S |
| UPC | 078316421143 |
| List Price | \$632 |



[View Larger](#)

Publications/Resources

[SEHA36AT0060](#)

Additional Resources for Spectra RMS™ Electronic Trip

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)

[Installation and Instruction](#)

[Time Current Curves](#)

[White Papers](#)

[BIM Files](#)

[Buy Log :3-47](#)

Spectra RMS Molded Case Circuit Breakers (SE150, SF250, SG600 and SK1200) have a digital, solid state, RMS sensing trip system with field installable, front-mounted rating plugs to establish or change the breaker ampere rating. Adjustable instantaneous with tracking short-time is standard on all frames. The trip system uses digital sampling to determine the RMS value of sinusoidal and non-sinusoidal currents.



ORLWDWIDE PARTNER