



**Search Parameters:**

[e-Catalog](#) > [Load Centers](#) > Commercial/High-rise Residential

**Load Centers, Commercial/High-rise Residential**

Product #: TL18415C

Short Description: MAIN LUG 150A 18CRT COMBO LD CENTER

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	Three Phase
Input/Output Voltage	208Y/120V ac
Type	Standard
Interrupting Capacity Rating	65
Amperage	150A
Device Type	Main Lugs
Enclosure	Indoor Type 1 Enclosure, Combination
UL/CUL Listing	UL
Phase	3 Phase
Socket Type	0
1" Space	18
1/2" Space	0
Feed	Either
Door	Yes
GSA Compliance	No
GO Schedule	137
List Price	\$328



[View Larger](#)

**Publications/Resources**

[TL18415C](#)

**Additional Resources for Three Phase**

[Drawings-Outline and Dimensional](#)

[Buy Log :1-14](#)

- UL Listed (Panelboards No. 67)
- 60°/75°C Conductor Rating
- Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code
- 22kAIC RMS symmetrical, Except Where Noted
- 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down
- For a listing of CSA Listed load centers, visit [www.geelectrical.com](http://www.geelectrical.com)



ORLWIDE PARTNER