



Color:  Gray

UPC Code: 07847705731

NEMA:  
5-15R



## 8200-IGG

### Item Description

Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Hospital Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Gray

### Technical Information

#### AC Horsepower Ratings

**At Rated Voltage:** 1/2 HP

#### Electrical Specifications

**Amperage:** 15 A

**Dielectric Voltage:** Withstands 3000V min

**Grounding:** Self-Grounding

**Pole:** 2

**Temperature Rise:** Max 30C temperature rise at full rated current

**Voltage:** 125 VAC

**Wire:** 3

#### Environmental Specifications

**Flammability:** Rated V-2 per UL 94

**Operating Temperature:** -40°C to 60°C

#### Material Specifications

**Body Material:** PBT Polyester Blend

**Clamp Nuts:** 0.030" Brass

**Color:** Gray

**Face Material:** PBT Polyester Blend

**Ground Clips:** Brass

**Ground Contacts:** 0030" Brass

**Grounding Screw:** #8 Hex Head, Triple-Drive Bass

**Line Contacts:** 0.030" Phosphor Bronze

**Mounting Screws:** Triple-Drive Plated Steel

**Shutter Mechanism:** Acetal

**Strap Material:** Steel (Galvanized G60)

**Terminal Screws:** #8 Triple-Drive Brass

#### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal Accom.:** 14-10 AWG

**Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

**Termination:** Back or Side Wire

**Wire Type:** Stranded or Solid

#### Product Features

**Color:** Gray

**Device Type:** Duplex Receptacle Outlet

**Feature 4:** Smooth Face

**Function:** Isolated Ground

**Grade:** Heavy-Duty Hospital Grade

**NEMA:** 5-15R

#### Standards and Certifications

**ANSI:** C-73

**Applicable Standards:** UL 498, Fed Spec W-C-569, CSA 22.2 No. 42


**Certification/Listing:** cULus, NOM-ANCE

**NEMA:** WD1 & WD 6

**NOM:** 057

**RoHS:** RoHS Compliant

**Warranty:** 10 Year Limited



Drawing Applies to 15 & 20A Devices

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

