



BURNDY Catalog Number
UPC Number
Description
Status

YA32LTC12FX
7818100202344
CU HYLUG 313.1 MCM FLEX
Active

Web Use
BURNDY Product Line

Dimensional

Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
Strip Length

Straight
2.93
Standard
Chamfered
0.52
Standard
0.19
1.19
1.40
1-1/4

General

Number of Holes
Product Description

1
Copper Compression Lug, 1 Hole
w/ Inspection Window, 300 Flex,
1/2" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

300 kcmil
300 kcmil
300 kcmil
N/A
313.1 (775/#24) DLO
N/A

Physical

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Tin
1/2
Red
Y
18,324
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

Y
Y
Compliant
N
N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175