

Interactive @Catalog

# Catalog Home

#### **Product Datasheet** CHANCE

## M3D67BR -- M3 Switch



25 kV, 125kV, 600 A, Single-Phase Hookstick Disconnect Switch

Product Specifications	
Overhead Product	Single Phase - Distribution Disconnect Switch (Crossarm Mounted)
Voltage(BIL)	25kV (125kV)
Rated Current	600 A
Insulator Type	ESP™ Polymer (2 1/4" Bolt Circle)
Base Type	Distribution Base, Serrated Slots
Carraige Bolt Length	8" (203 mm)
Captive Hardware	No
Terminal Connectors (ATC 1343)	No
Open Position Latch (160° Opening)	No
Bypass Studs	Yes
Nominal Voltage	25 kV
Maximum System Voltage	27kV
BIL (LIW)	125kV
Rated 60 Htz Withstand; Dry (Wet)	50kV (45kV)
Continuous Current Rating	630 A
8hr Emergency Overload	1080 A
Momentary Current Rating	40kA, asymmetrical
Short Time Withstand Current (2 sec)	25kA, symmetrical
Short Time Withstand Current (3 sec)	16kA, symmetrical
Maximum Temperature Rise @ 600A	28°C
Insulator Color	Dark Gray
Leakage Distance (Insulator)	21.9" (556.3mm)
Dry Arcing Distance (Insulator)	21.9" (556.3mm)
Cantilever (Insulator)	8.1" (205.7mm)
Tension (Insulator)	1,000 Lbs (4.45kN)
Torsion (Insulator)	5000 Lbs ( 22.24kN)

Compression (Insulator)	3,000 in Lbs (339 N-M)
Base Material	Galvanized Steel per ASTM A153
Base Description	Distribution Base, Serrated Slots with four 3/8" Carriage Bolts and backstrap
Dead-ending (Working Load)	8,000 Lbs
Blade(s)	Solid Copper (two blade truss-member)
Hinge(s)	Silver / Silver
Contact(s)	Silver / Silver
Terminal Pads	NEMA two-hole, Tin-plated Copper
Governing Standards	All Applicable ANSI/IEEE Standards
Drawing	Click <b>HERE</b> to view drawing of switch
Crated Weight	38.71 lbs
Material Type	Non-Standard
UPC Code	09635935839
Standard Package	1
Standard Package Unit	Each
Min Order Qty	1
Weight / Ea.	38.71 lbs

## **Compressed Product Number**

M3D67BR

# Catalog Home



## **Warranty Info** | **Trademarks** | **Terms of Use**

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.