Product data sheet Characteristics

UTH7330T METER SOCKET RINGLESS LEVER OH/UG 320A 3PH

Product availability: Stock - Normally stocked in distribution facility





Main

| Product or component type | Meter Socket |
|---------------------------|------------------------|
| Meter socket type | Ringless |
| Hub type | A-L ACPL closing plate |

Complementary

| Number of jaws 5 with jaw release Bypass type Lever bypass Phase 3 phases System Voltage 600 V AC Enclosure material Steel Electrical connection Studs 0.375" hex Service feed location OH UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) 350 kcmil for2 cable(s) (aluminium/copper) | Meter socket rated current | 320 A | |
|---|----------------------------|--------------------|--|
| Phase 3 phases System Voltage 600 V AC Enclosure material Steel Electrical connection Studs 0.375" hex Service feed location OH UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Number of jaws | 5 with jaw release | |
| System Voltage 600 V AC Enclosure material Steel Electrical connection Studs 0.375" hex Service feed location OH UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Bypass type | Lever bypass | |
| Enclosure material Electrical connection Studs 0.375" hex Service feed location OH UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Phase | 3 phases | : : |
| Electrical connection Studs 0.375" hex Service feed location OH UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | System Voltage | 600 V AC | |
| Service feed location OH UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Enclosure material | Steel | <u>. </u> |
| UG Wiring configuration 3-wire Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Electrical connection | Studs 0.375" hex | |
| Device mounting Surface AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Service feed location | | + + + 2 9 |
| AWG gauge 600 kcmil for1 cable(s) (aluminium/copper) | Wiring configuration | 3-wire | |
| | Device mounting | Surface | |
| | AWG gauge | | |

Environment

| Product certifications | UL listed | pot |
|---------------------------|-----------|---------|
| NEMA degree of protection | NEMA 3R | tion is |

Ordering and shipping details

| Category | 00039 - METER SOCKETS & HUBS |
|-------------------|------------------------------|
| Discount Schedule | DE4 |

| GTIN | 00785901145592 |
|-----------------------|----------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 62 |
| Returnability | N |
| Country of origin | US |

Offer Sustainability

| Will be compliant on 3Q2014 |
|---|
| Will be compliant on 3Q2014 |
| Reference not containing SVHC above the threshold |
| Reference not containing SVHC above the threshold |
| _ |

Contractual warranty

| Warranty period | 18 months | |
|-----------------|-----------|--|
| Warranty period | 18 months | |