Product data sheet Characteristics

QO2030

QO Tandem Mini Circuit Breaker 20/30A 1P 120/240V 10kA Plug-in Mount

Product availability: Stock - Normally stocked in distribution facility







Main

Man		
Product or component type	Miniature circuit-breaker	
Range of product	QO	
Line Rated Current	30 A	ب
	20 A	,
System Voltage	120/240 V AC	-
Mounting mode	Plug-in	
Poles description	1P	
Circuit breaker type	Tandem	
Circuit breaker application	HACR rated	
Electrical connection	Box lugs	
		 :

Complementary

Breaking capacity	10 kA at: 120/240 V AC	
Number of spaces required	1	
AWG gauge	AWG 14AWG 8 (copper or aluminium)	7

Environment

Product certifications	UL listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00181 - REPLCMNT TANDEMS - DO NOT NEGOTIATE	
Discount Schedule	DE2A	
GTIN	00785901001010	
Nbr. of units in pkg.	1	

Package weight(Lbs)	0.3300000000000002	
Returnability	Υ	
Country of origin	MX	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months