Product data sheet Characteristics

EGB24040 MINIATURE CIRCUIT BREAKER 480Y/277V 40A

Product availability: Stock - Normally stocked in distribution facility





Price*: 776.00 USD



Main

Range of product	125 A Frame EDB-EGB-EJB	, L
Product or component type	Miniature circuit-breaker	7
Device short name	EGB	
Module type	E-Frame	-
Trip unit rating	1800 A	<u>.</u>

Complementary

Complementary		-
Line Rated Current	40 A	
System Voltage	480Y/277 V AC	
AWG gauge	AWG 12AWG 2/0 aluminium AWG 14AWG 2/0 copper	lead for determining
Breaking capacity	35 kA 480Y/277 V AC 65 kA 240 V AC	900
Circuit breaker application	HACR rated HID rated	is to the
Depth	4.05 in	
Electrical connection	Lugs	n heriti in for
Height	5.66 in	
Holding current	630 A	a
Local signalling	Trip indicator	
Mounting mode	Bolt-on	ote interval
Number of poles	2	
Number of spaces	2	<u></u>
Number of spaces required	2	to the
Product destination	Panelboard NF	oc.
Product weight	3 lb(US)	ب ه ب
Protection type	Short-circuit Overload	iei P

Width	1.96 in

Environment

Product certifications	CSA UL listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00936 - EGB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	00785901130314
Nbr. of units in pkg.	1
Package weight(Lbs)	2.48
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1423 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	