

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1224.00 USD



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	1500 VA
Primary voltage	230 x 460 V 240 x 480 V 220 x 440 V
Secondary voltage	115/230 V 110/220 V 120/240 V
Range of product	T

### Complementary

Phase	1 phase
Rated power in VA	1500 VA per UL 1500 VA per CSA 1500 VA per NOM 1000 VA per CE
Primary voltage	220 x 440 V : 110/220 V 230 x 460 V : 115/230 V 240 x 480 V : 120/240 V
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	6.17 in
Width	7.06 in
Depth	5.92 in
Material	Copper winding
Product compatibility	FSC2

### Environment

Product certifications	CE CSA file LR37055 guide 184-N-90
------------------------	---------------------------------------

UL listed file E61239

NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

### Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901803720
Nbr. of units in pkg.	1
Package weight(Lbs)	38
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	10 years
-----------------	----------