Product data sheet Characteristics

QOB250VH1021

QO Miniature Circuit Breaker 50A 2P 120/240V 22kA Bolt-on Mount, Shunt Trip

Product availability: Stock - Normally stocked in distribution facility







Main

Product or component type	Miniature circuit-breaker	
Range of product	QO	
Line Rated Current	50 A	
System Voltage	120/240 V AC	
Mounting mode	Bolt-on	
Poles description	2P	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	·
Electrical connection	Box lugs	
Accessory / separate part type	Shunt trip, AC,	

Complementary

Breaking capacity	22 kA at: 120/240 V AC	
Number of spaces required	3	
AWG gauge	AWG 8AWG 2 (copper or aluminium)	
Height	3.12 in	
Depth	2.91 in	
Width	2.25 in	

Environment

		ç
Product certifications	CSA UL listed	i
Ambient air temperature for operation	104 °F (40 °C)	— Jeinfai

Ordering and shipping details

Category	00015 - QOB CIRCUIT BREAKERS

Discount Schedule	DE2	
GTIN	00785901729051	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1	
Returnability	N	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months