

Eaton NON-35

Catalog Number: NON-35

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 35 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 125 Vdc|50 kAIC at 250 Vac, Standard, 10, 250 V, 125 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series NON fuse	NON-35
UPC	Product Length/Depth
051712101608	3 in
Product Height	Product Width
0.81 in	0.81 in
Product Weight	Warranty
0.1 lb	Not Applicable
Compliances	
CE Marked	

Product specifications

Fuse indicator

Non-indicating

Special features

Non current limiting

Interrupt rating

50 kAIC at 250 Vac

50 kAIC at 125 Vdc

Type

Supplemental one-time fuse

Connection

Ferrule end x ferrule end

Quantity

10

Class

Class H

Voltage rating

250 Vac, 125 Vdc

Application

Light duty circuit locations

Amperage Rating

35 A

Packaging type

Standard

Resources

Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-35

Technical data sheets

NON-35~BUSS ONE TIME FUSE

Technical service bulletins

Datasheet - FNQ-30