

Eaton NON-40

Catalog Number: NON-40

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 40 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 250 Vac|50 kAIC at 125 Vdc, Standard, 10, 250 V, 125 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series NON fuse	NON-40
UPC	Product Length/Depth
051712101615	3 in
Product Height	Product Width
0.81 in	0.81 in
Product Weight	Warranty
0.01 lb	Not Applicable
Compliances	
CE Marked	



Electrical rating

Amperage Rating

40 A

Interrupt rating

50 kAIC at 250 Vac

50 kAIC at 125 Vdc

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

General information

Class

Class H

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

Resources

Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-40

Technical data sheets

NON-40~BUSS ONE TIME FUSE

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)