Eaton LP-CC-4

Catalog Number: LP-CC-4

Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 4 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 150 Vdc|200 kAIC at 600 V, Melamine tube, Standard, 10

General specifications



Catalog Number

Eaton Bussmann series LP-CC fuse

LP-CC-4

UPC

EAN

051712180320

5704057051187

Product Length/Depth

Product Height

1.5 in

0.41 in

Product Width

Product Weight

0.41 in

0.15 lb

Warranty

Compliances

Not Applicable

CE Marked

RoHS Compliant





Product specifications

Fuse indicator

Non-indicating

Special features

Rejection style

Interrupt rating

20 kAIC at 150 Vdc 200 kAIC at 600 Vac

Number of elements

Dual

Connection

Ferrule end x ferrule end

Response time

12 sec at 200%

Quantity

10

Material

Melamine tube

Amperage Rating

4 A

Type

Current-limiting time-delay fuse

Class

Class CC

Voltage rating

600 Vac, 150 Vdc

Application

Specialized circuits and industrial control

Packaging type

Standard

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

LP-CC-4~LOW PEAK CC TIME DELAY

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - LP-CC-4

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia