### **Product specifications**

# Eaton SC-60

# Catalog Number: SC-60

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 60 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 10 kAIC at 300 Vdc|100 kAIC at 480 Vac, Standard, 480 V, 300 Vdc

#### General specifications

**Product Name** 

Eaton Bussmann series SC fuse

**UPC** 

051712250603

Product Height

0.41 in

**Product Weight** 

0.35 lb

Compliances

CE Marked

**RoHS Compliant** 

Catalog Number

SC-60

Product Length/Depth

2.25 in

Product Width

0.41 in

Warranty

Not Applicable



# Electrical rating

Amperage Rating

60 A

Interrupt rating

10 kAIC at 300 Vdc 100 kAIC at 480 Vac

Response time

12 sec at 200%

Voltage rating

480 Vac, 300 Vdc

### Physical details

Packaging type

Standard

### General information

Class

Class G

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Rejection style

#### Resources

#### Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - SC-60

Technical data sheets

Bussmann series SC Class G Fuse Data Sheet No. 1024

SC-60~BUSS SC FUSE CLASS G CLASS G

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia