Eaton NON-4

Catalog Number: NON-4

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 4 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 250 Vac|50 kAIC at 125 Vdc, Standard, 10, 250 V, 125 Vdc

General specifications

Product Name	Catalog Num
Eaton Bussmann series NON fuse	NON-4
UPC	EAN
051712300049	5027590065
Product Length/Depth	Product Heig
0.56 in	2 in
Product Width	Product Weig
0.56 in	0.35 lb
Warranty	Compliances
Not Applicable	CE Marked







Electrical rating

Amperage Rating

4 A

Interrupt rating

50 kAIC at 250 Vac 50 kAIC at 125 Vdc

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

General information

Class

Class H

Connection Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

Resources

Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets Eaton Specification Sheet - NON-4

Technical data sheets NON-4~BUSS ONE TIME FUSE

Technical service bulletins Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia