# Eaton FWH-40B

## Catalog Number: FWH-40B

Eaton Bussmann series FWH high speed fuse, 750 Vac, 750 Vdc, 40A, 200 kAlC at 1000 Vac, 50 kAlC at 500 Vdc, None, High speed fuse, Blade end X blade end, Stud

### General specifications

#### **Product Name**

Eaton Bussmann series high speed

cylindrical fuse

UPC

051712795753

Product Length/Depth

108 mm

**Product Width** 

90 mm

Warranty

Not Applicable

Certifications

UL Recognized CSA Certified

Catalog Number

FWH-40B

Model Code

40A 500V AC TAG HIGH SPEED FUSE

EAN

5027590499651

**Product Height** 

28 mm

**Product Weight** 

63.6 g

Compliances

**CE Marked** 



## **Product specifications** Rated voltage DC 500 V Interrupt rating 50 kAIC at 500 Vdc 200 kAIC at 1000 Vac Center-to-center distance of connections 60.75 mm Insulated metal gripping lugs (IMGL) No Current type AC/DC Mounting method Stud **Amperage Rating** 40 A Fuse type FWH-B Fuse system (according to IEC 60269) Other Rated switching capacity 200 kA Voltage rating 500 Vac, 500 Vdc Fuse indicator Non Indicating Construction size Other Clearing (I2T) 320 Rated voltage AC 500 V

Color None

Connection

Blade end x blade end

#### Resources

#### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

#### Mounting dimension

M8

#### Utilization category

aR (accompanied semiconductor protection)

#### Watt losses

7.5 W

#### Type

High speed fuse

#### Fuse shape

Cylindrical, center bolted tags

#### Breaking capacity

200 kA

#### Class

Class aR

#### Pre arc (I2T)

76

#### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

#### Voltage type

AC/DC



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia