

3M Science.
Applied to Life.™

Connecting made simple.

Solutions for easy
disconnects and additions.



3M™ Medium Voltage
Separable Connectors

3M.com/Energy



3M separable connector solutions

3M offers separable connector solutions up to 35 kV for connecting electrical cable and equipment. The 3M™ Deadbreak Elbow Connectors, 600 A connect equipment and cable on primary feeder and network circuits. 3M™ Loadbreak Elbow Connectors, 200 A are fully shielded and insulated plug-in separable connectors used for connecting underground cable to transformers, switchgear and junctions equipped with loadbreak bushings.

Table of contents

3M Deadbreak Elbow Connectors, 600 A

Overview	4
Selection Tables	5–6
Accessories Ordering Information.....	7–9

3M Loadbreak Elbow Connectors, 200 A

Overview	11
Selection Tables	12–13
Accessories Ordering Information.....	14–16
Contact Information	17
Important Notice.....	18



3M™ Deadbreak Elbow, Connectors, 600A



Overview



3M™ Deadbreak Elbow Connector, 600 A

3M Deadbreak Elbow Connectors, 600 A and accessories from 3M provide an easy way to terminate cables and equipment, and splice primary cable at 25/28 kV and 35 kV. It is fully shielded and features a bolted connection in aluminum and terminates or splices power cables with copper or aluminum conductors ranging in size from #2 AWG to 1500 kcmil.

All deadbreak products and accessories meet or exceed all applicable requirements of:

- ANSI/IEEE Std 386™ for separable insulated connector systems
- IEEE Std 592™ for exposed semiconducting shields

Voltage Class, Phase-to-Phase	Product Ratings	
	25/28 kV	35 kV
Maximum Operating Line-to-Ground Voltage	16.2 kV	21.1 kV
Corona Voltage Level (partial discharge extinction voltage)	21.5 kV	26 kV
AC Withstand, 1 Minute	45 kV	50 kV
Impulse-Withstand Voltage (BIL)	125 kV	150/200 kV
Continuous Current		
Aluminum	600 A	
Copper	900 A	
Short-time Current		
Aluminum	25 kA, 0.17 s - 10 kA, 3 s	
Copper	40 kA, 0.17 s - 10 kA, 3 s	

All 3M Deadbreak Elbow Connectors, 600 A are 100% Production-tested for PD and Either AC or BIL.

Voltage Class, Phase-to-Phase	Product Ratings	
	25/28 kV	35 kV
Corona Voltage Level (partial discharge extinction voltage)	21.5 kV	26 kV
AC Withstand, 1 Minute	45 kV	50 kV
Impulse-Withstand Voltage (BIL)	125 kV	150/200 kV

Selection tables

3M™ Deadbreak Elbow 25/28 kV, 600 A

3M™ Deadbreak Elbow 625-Series includes 25/28 kV 600 A Elbow with test point, stud, lug, insulating plug with end cap and jacket seal.



Table W1 Cable Adapter	
Code	Insulation Range
E	0.530 in. – 0.680 in. (13.5mm – 17.3mm)
F	0.640 in. – 0.820 in. (16.3mm – 20.8mm)
G	0.760 in. – 0.950 in. (19.3mm – 24.1mm)
H	0.850 in. – 1.050 in. (21.6mm – 26.7mm)
J	0.980 in. – 1.180 in. (24.9mm – 30.0mm)
K	1.090 in. – 1.310 in. (27.7mm – 33.3mm)
L	1.180 in. – 1.465 in. (30.0mm – 37.2mm)
LM	1.280 in. – 1.430 in. (32.5mm – 36.3mm)
M	1.370 in. – 1.630 in. (34.8mm – 41.4mm)
N	1.515 in. – 1.780 in. (38.5mm – 45.2mm)
P	1.725 in. – 1.935 in. (43.8mm – 49.1mm)

Table X Lug			
Code Shearbolt	Code Compression	Concentric/ Compressed	Compact/ Solid
SB1	22	#2	#1
	23	#1	1/0
	24	1/0	2/0
	25	2/0	3/0
	26	3/0	4/0
	27	4/0	250
SB2	28	250	300
	29	300	350
	30	350	400
	32	450	500/550
SB3	33	500	600
	35	600	700
	36	650	750/800
	38	700/750	900
SB4	39	800	900
	40	900	1,000
	41	1,000	—
	44	1,250	—

Note: For other 25/28 kV applications, please contact your sales representative for details.

Note: Please contact a 3M Representative for more information if you are unsure which product you need.

Selection tables

3M™ Deadbreak Elbow 35 kV, 600 A

3M™ Deadbreak Elbow 635-Series includes 35 kV 600 A Elbow with test point, stud, lug, insulating plug with end cap and jacket seal.



Table W2 Cable Adapter	
Code	Insulation Range
D	0.750 in. – 0.985 in. (19.1mm – 25.0mm)
E	0.930 in. – 1.040 in. (23.6mm – 26.4mm)
F	0.980 in. – 1.115 in. (24.9mm – 28.3mm)
G	1.040 in. – 1.175 in. (26.4mm – 29.9mm)
H	1.095 in. – 1.240 in. (27.8mm – 31.5mm)
J	1.160 in. – 1.305 in. (29.5mm – 33.2mm)
K	1.220 in. – 1.375 in. (31.0mm – 34.9mm)
L	1.285 in. – 1.395 in. (32.6mm – 35.4mm)
M	1.355 in. – 1.520 in. (34.3mm – 38.6mm)
N	1.485 in. – 1.595 in. (37.7mm – 40.5mm)
P	1.530 in. – 1.640 in. (38.9mm – 41.7mm)
Q	1.575 in. – 1.685 in. (40.0mm – 42.8mm)
R	1.665 in. – 1.785 in. (42.3mm – 45.3mm)
S	1.755 in. – 1.875 in. (44.6mm – 47.6mm)
T	1.845 in. – 1.965 in. (46.9mm – 49.9mm)
U	1.935 in. – 2.055 in. (49.2mm – 52.2mm)
V	2.025 in. – 2.145 in. (51.4mm – 54.5mm)

Table X Lug			
Code Shearbolt	Code Compression	Concentric/ Compressed	Compact/ Solid
SB1	22	#2	#1
	23	#1	1/0
	24	1/0	2/0
	25	2/0	3/0
	26	3/0	4/0
	27	4/0	250
SB2	28	250	300
	29	300	350
	30	350	400
	32	450	500/550
SB3	33	500	600
	35	600	700
	36	650	750/800
	38	700/750	900
SB4	39	800	900
	40	900	1,000
	41	1,000	—
	44	1,250	—
*	—	1,500	—

Note: For other 35 kV applications, please contact your sales representative for details.

Note: Please contact a 3M Representative for more information if you are unsure which product you need.

Ordering information



3M™ Deadbreak Component, Connecting Plugs, 600 A

Part Number	Description	Quantity
625CP	600 A Connecting Plug 25/28 kV	1/box
635CP	600 A Connecting Plug 35 kV	1/box



3M™ Deadbreak Cable Adapters

Part Number	Description	Quantity
625CAw1	Deadbreak Adapter, 25/28 kV (refer to table W1 on page 4)	1/box
635CAw2	Deadbreak Adapter, 35 kV (refer to table W2 on page 5)	1/box



3M™ Deadbreak Component, Insulating Plug w/ Caps, 600 A

Part Number	Description	Quantity
625IPC	Insulating Plug with Cap, 25/28 kV	1/box
635IPC	Insulating Plug with Cap, 35 kV	1/box



3M™ Deadbreak Component, Elbow Insulating Caps, 600 A

Part Number	Description	Quantity
625IC	Insulating Cap, 25/28 kV Deadbreak	1/box
635IC	Insulating Cap, 35 kV Deadbreak	1/box



3M™ Deadbreak Component, Aluminum Studs, 600 A

Part Number	Description	Quantity
625ALSTUD	Aluminum Stud, 5/8"-11 UNC Threaded, 25/28 kV	1/box
635ALSTUD	Aluminum Stud, 5/8"-11 UNC Threaded, 35 kV	1/box



3M™ Deadbreak Component Shearbolt and Crimp Lugs, 600 A

Part Number	Description	Quantity
xAL	Deadbreak AL Compression Lug, 25/28 kV, 35kV	1/box
SBx	Deadbreak Shearbolt Lug, 25/28 kV, 35kV	1/box
QLSx	Premium Shearbolt Lug, 25/28 kV, 35kV	1/box

Note: For compression code, refer to Table X on pages 5.

3M™ Silicone Lubricant Grease

Part Number	Description	Quantity
Silicone Lube	Silicone Lubricant Grease	4g/packet

Ordering information

3M™ Deadbreak Elbow Bushing Extenders, 600 A



3M Deadbreak Elbow Bushing Extenders, 600 A is used to increase the distance between the 600 A bushing interface and the 600 A T-body. The extender is insulated and shielded to protect dead front integrity.

Part Number	Description	Quantity
625BX	Bushing Extender, 25/28 kV Deadbreak	1/box
635BX	Bushing Extender, 35 kV Deadbreak	1/box

3M™ Loadbreak Elbow Reducing Tap Plugs, 600 A



3M Loadbreak Elbow Reducing Tap Plugs, 600 A adds a 200 A loadbreak interface to an existing 600 A deadbreak T-Body. It is used for adapting an existing 600 A elbow to a 200 A tap or for different applications. It can be used for installing surge arrestors, testing or grounding 600 A systems. The Elbow Tap Plug (ETP) is fault close rated to 10,000 A and complies with IEEE Std 386™.

Part Number	Description	Quantity
615RTP	600 A Reducing Tap Plug, 15 kV	1/box
625RTP	600 A Reducing Tap Plug, 25/28 kV	1/box
635RTP	600 A Reducing Tap Plug, 35 kV, Small Interface (IEEE int. 7B)	1/box

3M™ Cold Shrink Shield Adapter Kits 8459/8460 Series for Bottom Seal



3M Cold Shrink Shield Adapter Kits 8460 Series accommodates the grounding of accessories installed on conventional tape, longitudinally corrugated (LC), wire and UniShield® Power Cables. The 3M Shield Adapter Kit design provides a fault current capacity of 600 A on 15–35 kV class cables.

Part Number	Description	Quantity
8459	Jacket OD Range, 0.59 in. – 1.05 in. (15.0mm – 26.6mm)	1/box
8460	Jacket OD Range, 0.83 in. – 1.64 in. (21.1mm – 41.6mm)	3/box
8461	Jacket OD Range, 1.27 in. – 2.17 in. (32.3mm – 55.1mm)	1/box
8462	Jacket OD Range, 1.70 in. – 2.60 in. (43.2mm – 66.0mm)	1/box

Ordering information

3M™ Deadbreak Junction Bars, 600 A

3M Deadbreak Junction Bars, 600 A sectionalize feeders or provide a lateral tap. They can be installed in pad-mounted equipment or in a subsurface vault application. They are also fully-shielded and fully submersible and can be interfaced with all standard 600 A class separable connectors. Additionally, 3M Deadbreak Junction Bars, 600 A conform to all applicable requirements of IEEE Std 386™ and IEEE Std 592™.

Pre-molded 3M junctions are available in two, three and four point configurations. 3M Deadbreak Junction Bars, 600 A products contain an aluminum bus bar and mate with any 25/28 kV or 35 kV rated separable connector.



Part Number	Description	Quantity
3M Deadbreak Junction Bars, 600 A (with brackets)		
625J2B	Deadbreak Junction Bar, 25/28 kV, 2-Way	1/box
625J3B	Deadbreak Junction Bar, 25/28 kV, 3-Way	1/box
625J4B	Deadbreak Junction Bar, 25/28 kV, 4-Way	1/box
635J2B	Deadbreak Junction Bar, 35 kV, 2-Way	1/box
635J3B	Deadbreak Junction Bar, 35 kV, 3-Way	1/box
635J4B	Deadbreak Junction Bar, 35 kV, 4-Way	1/box
3M Deadbreak Junction Bars, 600 A (with U-Straps)		
625J2U	Deadbreak Junction Bar, 25/28 kV, 2-Way	1/box
625J3U	Deadbreak Junction Bar, 25/28 kV, 3-Way	1/box
625J4U	Deadbreak Junction Bar, 25/28 kV, 4-Way	1/box
635J2U	Deadbreak Junction Bar, 35 kV, 2-Way	1/box
635J3U	Deadbreak Junction Bar, 35 kV, 3-Way	1/box
635J4U	Deadbreak Junction Bar, 35 kV, 4-Way	1/box



3M™ Elbow Surge Arresters, 35 kV

The 3M™ Elbow Surge Arrester 635-SA Series is a gapless, metal oxide varistor (MOV) type arrester in a compact, deadfront EPDM insulated package, directly interfaceable with IEEE 386™ Interface 13 bushings (35 kV Class – 600A) without the need for adapters or reducers.

Part Number	Description	Quantity
3M™ Surge Arresters, 600 A		
635-SA27	Elbow Surge Arrester, 35 kV, DB, 22 kV MCOV/27 kV Duty Cycle	1/box
635-SA30	Elbow Surge Arrester, 35 kV, DB, 24.2 kV MCOV/30 kV Duty Cycle	1/box
635-SA33	Elbow Surge Arrester, 35 kV, DB, 27 kV MCOV/33 kV Duty Cycle	1/box
635-SA36	Elbow Surge Arrester, 35 kV, DB, 29 kV MCOV/36 kV Duty Cycle	1/box



**3M™ Loadbreak Elbow,
Connectors, 200A**



Overview



3M™ Loadbreak Elbow Connectors, 200 A

3M™ Loadbreak Elbow Connectors, 15 kV, 25/28 kV and 35 kV, 200 A are fully shielded, insulated, and submersible products that provide a means to mate or disconnect cable to switchgear, transformers, or sectionalizing equipment on power distribution systems. They are used for pad-mounted or subsurface applications, where the components may be exposed to direct sunlight or continuously submerged in water up to 6 feet (2m).

All loadbreak products and accessories meet or exceed all applicable requirements of:

- IEEE Std 386™ for separable connectors
- IEEE Std 592™ for exposed semi-conducting shields

Voltage Class, Phase-to-Phase	Product Ratings		
	15 kV	25/28 kV	35 kV
Maximum Operating Line-to-Ground Voltage	8.3 kV	16.2 kV	21.1 kV
Maximum Operating Phase-to-Phase Voltage	14.4 kV	28.0 kV	36.6 kV
Corona Voltage Level (partial discharge extinction voltage)	11 kV	21.5 kV	26 kV
AC Withstand, 1 Minute	34 kV	45 kV	50 kV
Impulse-Withstand Voltage (BIL)	95 kV	125 kV	150 kV

Continuous Current

Continuous Current 200 A

Short-time Current

0.17 s Duration 10,000 A RMS Symmetrical

3 s Duration 3,500 A RMS Symmetrical

All 3M Loadbreak Elbow Connectors, 200 A are 100% Production-Tested for PD and Either AC or BIL.

Voltage Class, Phase-to-Phase	Product Ratings		
	15 kV	25/28 kV	35 kV
Impulse-Withstand Voltage (BIL)	95 kV	125 kV	150 kV
Corona Voltage Level (partial discharge extinction voltage)	11 kV	21.5 kV	26 kV
AC Withstand, 1 Minute	34 kV	45 kV	50 kV

Selection tables

3M™ Loadbreak Elbow Connectors, 15 kV, 200 A

3M™ Loadbreak Elbow 215-Series includes 15 kV 200 A Elbow with test point, probe, lug and jacket seal.

2 1 5 L B W W X B

Table W Housing Size	
Code	Insulation Range Inches (mm)
30	0.495 in – 0.730 in (12.57 mm - 18.54 mm)
40	0.635 in – 0.905 in (16.13 mm - 22.99 mm)
50	0.760 in – 1.135 in (19.30 mm - 28.83 mm)

Table X Lug		
Code Compression	Concentric/ Compressed	Compact/ Solid
1	#6	#4
2	#4	#2
3	#2	#1
4	#1	1/0
5	1/0	2/0
6	2/0	3/0
7	3/0	4/0
8	4/0	250

3M™ Loadbreak Elbow Connectors, 25/28 kV, 200 A

3M™ Loadbreak Elbow 228-Series includes 25/28 kV 200 A Elbow with test point, probe, lug and jacket seal.

2 2 8 L B W W X B

Table W Housing Size	
Code	Insulation Range Inches (mm)
40	0.800 in – 1.140 in (20.32 mm - 28.96 mm)
50	0.920 in – 1.310 in (23.37 mm - 33.27 mm)

Table X Lug		
Code Compression	Concentric/ Compressed	Compact/ Solid
2	---	#2
3	#2	#1
4	#1	1/0
5	1/0	2/0
6	2/0	3/0
7	3/0	4/0
8	4/0	250

Note: All 3M complete kits come with the cold shrink bottom jacket seal and grounding options for multiple cable construction.

Note: Please contact a 3M Representative for more information if you are unsure which product you need.

Selection tables

3M™ Loadbreak Elbow Connectors Large Interface, 35 kV, 200 A (IEEE int. 8)

3M™ Loadbreak Elbow 235-Series includes 35 kV 200 A Elbow with test point, probe, lug and jacket seal.




Table W Housing Size	
Code	Insulation Range Inches (mm)
5	1.02 in. – 1.310 in. (25.91 mm - 33.27 mm)

Table X Lug		
Code Compression	Concentric/ Compressed	Compact/ Solid
4	---	1/0
5	1/0	2/0
6	2/0	3/0
7	3/0	4/0
8	4/0	250

3M™ Loadbreak Elbow Connectors Small Interface, 35 kV, 200 A (IEEE int. 7B)

3M™ Loadbreak Elbow 228-Series includes 25/28 kV 200 A Elbow with test point, probe, lug and jacket seal.




Table W Housing Size	
Code	Insulation Range inches (mm)
C30	0.846 in. – 1.051 in. (21.49 mm - 26.70 mm)
D40	0.976 in. – 1.181 in. (24.79 mm - 30.0 mm)
E50	1.087 in. – 1.311 in. (27.61 mm - 33.30 mm)

Table X Lug		
Code Compression	Concentric/ Compressed	Compact/ Solid
4	---	1/0
5	1/0	2/0
6	2/0	3/0
7	3/0	4/0
8	4/0	250

Note: All 3M complete kits come with the cold shrink bottom jacket seal and grounding options for multiple cable construction.

Note: Please contact a 3M Representative for more information if you are unsure which product you need.

Ordering information



3M™ Loadbreak Bi-Metal Lugs

All Bi-metal compression lug meets all requirements of ANSI Std C119.4 for Class A connectors.

Part Number	Description	Quantity
200LUGxB	Long Bi-Metal Lug, Standard	1/box

Note: For compression code, refer to Table X on page 12.

3M™ Loadbreak Probes



Part Number	Description	Quantity
215LBP	Probe Kit, Complete with Pin Wrench, 15 kV	1/box
228LBP	Probe Kit, Complete with Pin Wrench, 25/28 kV	1/box
235LBSP	Probe Kit, Complete with Pin Wrench, 35 kV, Small Interface	1/box
235LBLP	Probe Kit, Complete with Pin Wrench, 35 kV, Large Interface	1/box

3M™ Loadbreak Bushing Inserts

Internal hex broach accepts a 5/16 inch wrench for proper installation torque. Yellow seating indicator provides a positive indication that the mating product is fully installed.



Part Number	Description	Quantity
215LBI	Bushing Insert, 15 kV Loadbreak	1/box
228LBI	Bushing Insert, 25/28 kV Loadbreak	1/box

3M™ Loadbreak Insulating Caps

Used as a temporary or permanent cover on an energized operating interface. Standard product has an insulating cuff. The insulating cap is supplied with a 36 inch lead for grounding.



Part Number	Description	Quantity
215IC	Insulating Cap, 15 kV Loadbreak	1/box
228IC	Insulating Cap, 25/28 kV Loadbreak	1/box

Ordering information

3M™ Loadbreak Junction Bars, 200A

3M Loadbreak Junction Bars, 200A are used to sectionalize cables or as feed-thrus for making lateral tapes. They are available in two, three and four tap units. Adjacent taps are 4 inches center to center. Vented yellow seating (25 kV) indicator rings provide a positive indication that the mating product is fully installed and assists in minimizing no-load, partial vacuum flashovers..

Junctions with the corrosion-resistant stainless steel mounting bracket allow back plate mounting angles of 30, 45, or 60 degrees. This bracket can be adjusted for horizontal mounting to a flat surface. Junctions can also be ordered with only U-straps for horizontal surface mounting.



Part Number	Description	Quantity
3M Loadbreak Junction Bars, 200 A (with brackets)		
215J2B	200 A 2-Position Junction with Bracket, 15 kV	1/box
215J3B	200 A 3-Position Junction with Bracket, 15 kV	1/box
215J4B	200 A 4-Position Junction with Bracket, 15 kV	1/box
228J2B	200 A 2-Position Junction with Bracket, 25/28 kV	1/box
228J3B	200 A 3-Position Junction with Bracket, 25/28 kV	1/box
228J4B	200 A 4-Position Junction with Bracket, 25/28 kV	1/box
3M Loadbreak Junction Bars, 200 A (with U-Straps)		
215J2U	200 A 2-Position Junction with U-Strap, 15 kV	1/box
215J3U	200 A 3-Position Junction with U-Strap, 15 kV	1/box
215J4U	200 A 4-Position Junction with U-Strap, 15 kV	1/box
228J2U	200 A 2-Position Junction with U-Strap, 25/28 kV	1/box
228J3U	200 A 3-Position Junction with U-Strap, 25/28 kV	1/box
228J4U	200 A 4-Position Junction with U-Strap, 25/28 kV	1/box

Ordering information

3M™ Loadbreak Surge Arresters, 200 A


The 3M Loadbreak Surge Arresters, 200A are gapless, metal oxide varistor (MOV) devices, provide shielded arrester protection for medium voltage systems. The 3M 200 A Loadbreak Surge Arresters meet the relevant requirements of IEEE™ Std. C62.11 and IEEE™ Std. 386.



Part Number	Description	Quantity
3M™ Loadbreak Surge Arrester, 15 kV Interface		
215SA03	Loadbreak Surge Arrester, 2.55 kV MCOV, 3 kV Duty Cycle	1/box
215SA06	Loadbreak Surge Arrester, 5.1 kV MCOV, 6 kV Duty Cycle	1/box
215SA09	Loadbreak Surge Arrester, 7.65 kV MCOV, 9 kV Duty Cycle	1/box
215SA10	Loadbreak Surge Arrester, 8.4 kV MCOV, 10 kV Duty Cycle	1/box
215SA12	Loadbreak Surge Arrester, 10.2 kV MCOV, 12 kV Duty Cycle	1/box
215SA15	Loadbreak Surge Arrester, 12.7 kV MCOV, 15 kV Duty Cycle	1/box
215SA18	Loadbreak Surge Arrester, 15.3 kV MCOV, 18 kV Duty Cycle	1/box
3M™ Loadbreak Surge Arrester, 25/28 kV Interface		
225SA09	Loadbreak Surge Arrester, 7.65 kV MCOV, 9 kV Duty Cycle	1/box
225SA10	Loadbreak Surge Arrester, 8.4 kV MCOV, 10 kV Duty Cycle	1/box
225SA12	Loadbreak Surge Arrester, 10.2 kV MCOV, 12 kV Duty Cycle	1/box
225SA15	Loadbreak Surge Arrester, 12.7 kV MCOV, 15 kV Duty Cycle	1/box
225SA18	Loadbreak Surge Arrester, 15.3 kV MCOV, 18 kV Duty Cycle	1/box
225SA21	Loadbreak Surge Arrester, 17 kV MCOV, 21 kV Duty Cycle	1/box
3M™ Loadbreak Surge Arrester, 35 kV Small Interface		
235SAS24	Loadbreak Surge Arrester, Small Interface, 19.5 kV MCOV, 24 kV Duty Cycle	1/box
235SAS27	Loadbreak Surge Arrester, Small Interface, 22 kV MCOV, 27 kV Duty Cycle	1/box
235SAS30	Loadbreak Surge Arrester, Small Interface, 24.4 kV MCOV, 30 kV Duty Cycle	1/box
3M™ Loadbreak Surge Arrester, 35 kV Large Interface		
235SAL27	Loadbreak Surge Arrester, Large Interface, 22 kV MCOV, 27 kV Duty Cycle	1/box
235SAL30	Loadbreak Surge Arrester, Large Interface, 24.4 kV MCOV, 30 kV Duty Cycle	1/box
235SAL33	Loadbreak Surge Arrester, Large Interface, 26.9 kV MCOV, 33 kV Duty Cycle	1/box
235SAL36	Loadbreak Surge Arrester, Large Interface, 29 kV MCOV, 36 kV Duty Cycle	1/box



Take expert-led, online electrical training anytime, anywhere 24×7. [3M.com/Energy-Academy](https://www.3m.com/Energy-Academy)



View our full product portfolio offering, create sharable project lists, and more with our 3M Electrical App, available on the [App Store](#)[®].



Contact us at 1-800-245-3573 or [3M.com/Energy](https://www.3m.com/Energy)

Important Notice

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

Industrial Use Only.



Electrical Markets Division
13011 McCallen Pass Blvd, Bldg C.
Austin TX, 78753

Phone: 1-800-245-3573
Fax: 1-800-245-0329
Web: 3M.com/Energy

3M is a trademarks of 3M Company. All other trademarks are property of their respective owners.
© 3M 2024. All rights reserved. 80-6016-0923-5.