



Actual

Catalog Number: L-14-120-9-L
Product ID: 7TAG054410R0008
UPC Number: 78621008028
EAN Number: 05414363153856
Status: Active

Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 362.81mm (14.284 Inches), Width of 7.62mm (0.30 Inches), Thickness of 1.91mm (0.075 Inches), Tensile Strength Rating of 534 Newtons (120 Pounds), 50 Pack

- Application Tools: ERG120

North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Brand Name	Catamount
Type	Heavy Duty
Standard	UL E49405
Width	0.3 in ; 7.62 mm
Length	14.284 in ; 362.81 mm
Thickness	0.075 Inch/1.91mm
Bundle Diameter	0.187 Inches/4.76mm-4.0 Inches/101.6mm
Material	Nylon/Polyamide 6.6
Color	Natural
Lock Mechanism	Plastic Pawl
Tensile Strength	120 Pounds/534 Newtons

European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	7.62mm
Length belt/tape/tie	362.81mm
Tie thickness	1.91mm
Min. holding force	534N
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamide PA
Surface protection	Untreated
Halogen free	Y
Colour	Natural colour
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N
MIL approval	N

Packaging

Inner Quantity	50
Inner Dimensions (inches)	20x6x3
Outer Quantity	3000
Outer Dimensions (inches)	17.9x13.9x13.1
Weight Uom	13.75 lbs. per 1000

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000223
--------------------------------	------------

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com