



Main

Product	Double Throw Safety Switch
Current Rating	60 A
Certifications	UL Listed
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Voltage Rating	600 V AC 600 V DC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	10 Hp at 240 V AC 50...60 Hz for 1 phase motors conforming to NEC 240.6 20 Hp at 240 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 25 Hp at 480 V AC 50...60 Hz for 1 phase motors conforming to NEC 240.6 50 Hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 30 Hp at 600 V AC 50...60 Hz for 1 phase motors conforming to NEC 240.6 60 Hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 10 Hp 250 V DC 30 hp 600 V DC
Tightening torque	35 Lbf.In (3.95 N.m) 0.00...0.01 in ² (2.06...5.26 mm ²) AWG 14...AWG 10) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.37 mm ²) AWG 8) 45 Lbf.In (5.08 N.m) 0.02...0.03 in ² (13.3...21.15 mm ²) AWG 6...AWG 4) 50 lbf.in (5.65 N.m) 0.04...0.05 in ² (26.67...33.62 mm ²) AWG 3...AWG 2)
Width	11.96 in (303.78 mm)
Height	29.94 in (760.48 mm)
Maximum Depth	6.93 in (176.02 mm)

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901308676
Nbr. of units in pkg.	1
Package weight(Lbs)	35 lb(US) (15.88 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.30 in (26.162 cm)
Package 1 width	12.50 in (31.75 cm)
Package 1 Length	33.00 in (83.82 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------