

Product Number: 49943

Order Abbreviation: QTP 2x32T8/UNV ISN-SC

General Description: QTP2x32T8UNVISNSC 2-lamp 32wT8 Instant Start electronic ballast, universal voltage, normal ballast factor, 10-pk



Product Information

Abbrev. With Packaging Info.	QTP2x32T8UNVISNSC 10/CS 1/SKU
Ballast Factor	0.88
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6930
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.97
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Max Case Temperature	70°C



Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 50/60Hz.
- Minimum starting temperature: -20 F / -29 C