Product data sheet Characteristics

QO132L125G LOADCTR QO MLO 240V 125A 1PH 32SP NEMA 1

Product availability: Stock - Normally stocked in distribution facility





Main

| TTIGHT | |
|-----------------------------------|--------------|
| Product or component type | Load Center |
| Range of product | QO |
| Load center type | Main lugs |
| Line Rated Current | 125 A |
| Number of spaces | 32 |
| Short-circuit current | 65 kA |
| Number of circuits | 32 |
| Number of tandem circuit breakers | 0 |
| Phase | 1 phase |
| System Voltage | 120/240 V AC |
| | |

Complementary

| AWG gauge | AWG 6AWG 2/0 (aluminium/copper) | |
|---------------------------|--|---|
| NEMA degree of protection | NEMA 1 indoor | |
| Cover type | Order separately | |
| Electrical connection | Lugs | |
| Device composition | Grounding bar included (not installed) | |
| Electrical connection | Lugs | |
| Wiring configuration | 3-wire | |
| Material | Tin plated copper busbar | |
| Enclosure material | Welded sheet steel | |
| Surface finish | Baked enamel grey | |
| Box number | 8 | |
| Product certifications | UL listed | |
| Height | 661 mm | i |
| Width | 14.25 in (362 mm) | |

Ordering and shipping details

| Category | 00001 - QO 1PH LC,12-42 CKT,NEMA1 | |
|-----------------------|-----------------------------------|--|
| Discount Schedule | DE3A | |
| GTIN | 00785901353478 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 14.78000000000001 | |
| Returnability | Υ | |
| Country of origin | US | |

Offer Sustainability

| Not Green Premium product | |
|---|---|
| Compliant - since 1248 - Schneider Electric declaration of conformity | |
| Schneider Electric declaration of conformity | |
| Reference not containing SVHC above the threshold | |
| Reference not containing SVHC above the threshold | |
| duct end of life instructions Need no specific recycling operations | |
| | Compliant - since 1248 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| Warranty period | 18 months | |
|-----------------|-----------|--|