

# GVAE1

TeSys Deca Manual Starter and Protector, auxiliary contact block, 1 NO or NC, top mount, screw clamp



## Main

|                           |   |
|---------------------------|---|
| Range                     | TeSys<br>TeSys Deca                                     |
| Device short name         | GVAE  |
| Product or Component Type | Auxiliary contact block                                 |
| Product Compatibility     | GV2L<br>GV2P<br>GV2RT<br>GV3P<br>GV3L<br>GV2LE<br>GV2ME |
| Mounting Location         | Front side  |
| Pole contact composition  | 1 NO/NC   |
| Quantity per Set          | Set of 10   |

## Complementary

|   |  |
|---|--|
| [Ui] rated insulation voltage               | 300 V UL 508<br>300 V CSA C22.2 No 14<br>250 V IEC 60947-1   |
| [Ue] rated operational voltage              | 24...240 V AC<br>24...60 V DC  |
| [Ith] conventional free air thermal current | 2.5 A  |
| Protection type                             | GG fuse 10 A<br>GB2CB06 circuit breaker 10 A   |
| Mechanical durability                       | 100000 cycles  |
| Minimum switching current                   | 5 mA   |
| Minimum switching voltage                   | 17 V   |
| Rated operational power in VA               | 120 VA 110...120 V AC-15 100000 cycles<br>120 VA 230...240 V AC-15 100000 cycles<br>48 VA 24 V AC-15 100000 cycles<br>60 VA 48 V AC-15 100000 cycles |
| Rated operational power in W                | 15 W 48 V DC-13 100000 cycles<br>24 W 24 V DC-13 100000 cycles<br>9 W 60 V DC-13 100000 cycles   |
| Tightening torque                           | 12.39 lbf.in (1.4 N.m) screw clamp terminals   |
| Height                                      | 0.43 in (11 mm)  |
| Width                                       | 1.77 in (45 mm)  |
| Depth                                       | 1.14 in (29 mm)  |
| Net Weight                                  | 0.04 lb(US) (0.02 kg)  |

## Environment

|                              |                    |
|------------------------------|--------------------|
| Environmental characteristic | Normal environment |
| Product Certifications       | UKCA               |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

|                       |                                  |
|-----------------------|----------------------------------|
| Category              | 22367-MANUAL STR PROTECTOR - GV2 |
| Discount Schedule     | I11                              |
| GTIN                  | 3389110343427                    |
| Nbr. of units in pkg. | 1                                |
| Package weight(Lbs)   | 0.46 oz (13.0 g)                 |
| Returnability         | Yes                              |
| Country of origin     | CZ                               |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 0.43 in (1.1 cm)       |
| Package 1 width              | 2.36 in (6 cm)         |
| Package 1 Length             | 3.15 in (8 cm)         |
| Unit Type of Package 2       | BB1                    |
| Number of Units in Package 2 | 10                     |
| Package 2 Weight             | 4.94 oz (140.0 g)      |
| Package 2 Height             | 0.79 in (2 cm)         |
| Package 2 width              | 6.30 in (16 cm)        |
| Package 2 Length             | 6.69 in (17 cm)        |
| Unit Type of Package 3       | S02                    |
| Number of Units in Package 3 | 220                    |
| Package 3 Weight             | 7.46 lb(US) (3.385 kg) |
| Package 3 Height             | 5.91 in (15 cm)        |
| Package 3 width              | 11.81 in (30 cm)       |
| Package 3 Length             | 15.75 in (40 cm)       |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

---

GVAE1

