

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	AC Contactor
Name and address of the applicant	Schneider Electric Industries SAS 35 rue Joseph Monier 92500 Rueil-Malmaison France
Name and address of the manufacturer	Schneider Electric Industries SAS 35 rue Joseph Monier 92500 Rueil-Malmaison France
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	See additional page(s) for the listing of 3 factories
Ratings and principal characteristics	Ui:690V; Uimp:6kV; Ith:25A...50A; Utilization category: AC-1,AC-3,AC-4,AC-3e; Ue:AC230...690V; Ie:9.75A...38A
Trademark / Brand (if any)	Schneider Electric
Customer's Testing Facility (CTF) Stage used	N/A
Model / Type Ref.	LC1D25, LC2D25, LC1D32, LC2D32, LC1D38, LC2D38 LC1D183, LC2D183, LC1D253, LC2D253, LC1D323, LC2D323 LC1D256, LC2D256, LC1D326, LC2D326, LC1D386, LC2D386
Additional information (if necessary may also be reported on page 2)	See additional page(s) for further Additional information.
A sample of the product was tested and found to be in conformity with	IEC 60947-4-1:2023 IEC 60947-5-1:2024
As shown in the Test Report Ref. No. which forms part of this Certificate	CN2570P3 001

This CB Test Certificate is issued by the National Certification Body

TÜV Rheinland InterCert Kft., MEEI Division
H-1143 Budapest, Gizella út 51-57., Hungary
Web: www.tuv.com

Date: 2025-05-19

Signature:



Wencai Zhang

Additional information :

Type designation:

LC1 D25 3 M7 S207
 (1) (2) (3) (4) (5)

Possible values:

- (1): Basic product type:
 LC1:single contactor
 LC2:reversing contactor
- (2): Size:
 D18
 D25
 D32
 D38
- (3): Type of connection:
 Blank: Screw connection (not for D18)
 3: Spring connection (not for D38)
 6: Ring lug connection (not for D18)
- (4): Coil codes: see below table
- (5): Specification code
 Blank:standard version
 S207:railway industry specification(for ring lug connectiononly:dc/lc coil)
 XS207:railway industry specification (for ring lug connection only:dc/lc coil without bidirectional peak limiting diode)

Coil code tables:

AC coil(50/60Hz):

Coil code	Us (V)						
J7	12	K7	100	M7	220	T7	480
Z7	21	F7	110	P7	230	S7	500
B7	24	FE7	115	U7	240	SC7	575
C7	32	G7	120	W7	277	X7	600
CC7	36	FC7	127	Q7	380	YC7	660
D7	42	GC7	140	V7	400	Y7	690
E7	48	L7	200	N7	415	-	-
EE7	60	LE7	208	R7	440	-	-



Date: 2025-05-19

Signature:

as on page 1

Additional information :

DC coil :

Coil code	Us (V)						
AD	6	ED	48	GD	125	TD	305
JD	12	ND	60	PD	155	VD	348
ZD	20	SD	72	QD	174	RD	440
BD	24	DD	96	LD	200	WD	543
BND	32	KD	100	MD	220	SCD	575
CD	36	FD	110	UD	250	XD	600

DC coil (Low consumption):

Coil code	Us (V)						
AL	5	BL	24	NL	60	FL	110
JL	12	CL	36	SL	72	ML	220
ZL	20	EL	48	DL	96	UL	250

Ratings:

Model: LC1D183, LC2D183

AC-1: Ue/Ie: 230V/400V/440V/500V/690V/25A;

AC-3: Ue/Ie: 230V/15A, 400V/15.5A, 440V/18A, 500V/16A, 690V/11.7A;

AC-3e: Ue/Ie: 230V/15A, 400V/15.5A, 440V/18A, 500V/16A, 690V/11.7A;

AC-4: Ue/Ie: 230V/12.5A, 400V/12.92A, 440V/15A, 500V/13.42A, 690V/9.75A;

Ith: 25A

Model: LC1D25, LC2D25, LC1D256, LC2D256

AC-1: Ue/Ie: 230V/400V/440V/500V/690V/40A;

AC-3: Ue/Ie: 230V/20A, 400V/22A, 440V/25A, 500V/23A, 690V/17A;

AC-3e: Ue/Ie: 230V/20A, 400V/22A, 440V/25A, 500V/23A, 690V/17A;

AC-4: Ue/Ie: 230V/16.7A, 400V/18.34A, 440V/20.84A, 500V/19.2A, 690V/14.2A;

Ith: 40A

Model: LC1D253, LC2D253

AC-1: Ue/Ie: 230V/400V/440V/500V/690V/25A;

AC-3: Ue/Ie: 230V/20A, 400V/22A, 440V/25A, 500V/23A, 690V/17A;

AC-3e: Ue/Ie: 230V/20A, 400V/22A, 440V/25A, 500V/23A, 690V/17A;

AC-4: Ue/Ie: 230V/16.7A, 400V/18.34A, 440V/20.84A, 500V/19.2A, 690V/14.2A;

Ith: 25A



Date: 2025-05-19

Signature:

as on page 1

Additional information :

Model:LC1D32, LC2D32, LC1D326, LC2D326

AC-1:Ue/Ie:230V/400V/440V/500V/690V/50A;

AC-3:Ue/Ie:230V/27A, 400V/29A, 440V/32A, 500V/28A, 690V/21A;

AC-3e:Ue/Ie:230V/27A, 400V/29A, 440V/32A, 500V/28A, 690V/21A;

AC-4:Ue/Ie:230V/22.5A, 400V/24.2A, 440V/20.84A, 500V/19.2A, 690V/14.2A;

Ith:50A

Model:LC1D323, LC2D323

AC-1:Ue/Ie:230V/400V/440V/500V/690V/40A;

AC-3:Ue/Ie:230V/20A, 400V/22A, 440V/25A, 500V/23A, 690V/17A;

AC-3e:Ue/Ie:230V/20A, 400V/22A, 440V/25A, 500V/23A, 690V/17A;

AC-4:Ue/Ie:230V/16.7A, 400V/18.34A, 440V/20.84A, 500V/19.2A, 690V/14.2A;

Ith:40A

Model:LC1D38, LC2D38, LC1D386, LC2D386

AC-1:Ue/Ie:230V/400V/440V/500V/690V/50A;

AC-3:Ue/Ie:230V/31.7A, 400V/35A, 440V/38A, 500V/28A, 690V/21A;

AC-3e:Ue/Ie:230V/31.7A, 400V/35A, 440V/38A, 500V/28A, 690V/21A;

AC-4:Ue/Ie:230V/26.42A, 400V/29.2A, 440V/20.84A, 500V/19.2A, 690V/14.2A;

Ith:50A



Date: 2025-05-19

Signature:

as on page 1

Factories :

1. PT. Schneider Electric Manufacturing Batam
Jl Beringin Lot 4, Lot 208, Lot 15, Lot 16, DAN Lot 16A, Batamindo Industrial Park (BIP), Muka Kuning Kel.Muka Kuning Kec. Sungai Beduk -Batam, Indonesia
2. SCHNEIDER ELECTRIC INDIA Pvt. Ltd
SURVEY NO 215, VILLAGE - GAGILLAPUR MEDAK ROAD, RANGAREDDY DISTRICT, HYDERABAD 500043
India
3. SCHNEIDER ELECTRIC INDIA Pvt. Ltd
SY NO 99/1, MAMIDIPALLY, Mamidipalle, Balapur, Rangareddy 500108
India