

## NKCR.E164353 - AUXILIARY DEVICES

## Auxiliary Devices

See General Information for Auxiliary Devices

**SCHNEIDER ELECTRIC INDUSTRIES S A, DBA TELEMECANIQUE**

E164353

8001 Knightdale Blvd  
Knightdale, NC 27545 USA

**Investigated to ANSI/UL 508**

**Accessories for Handy Box** Model(s) ZBR M2

**Accessories, add-on square trims** Model(s) ZB5-AZ31

**Accessories, boots** Model(s) ZB2-BPX+, ZBPX+, ZBWX+

**Accessories, legend holders, legend plates, metal and plastic guards** Model(s) ZBC-YX+, ZBC-ZX+, ZBYX+, ZBZX+

**Accessories, padlockable flaps** Model(s) ZB4-BZ6X+

**Accessories, plugs** Model(s) ZB4-SZ3, ZB5-SZ3, ZB5-SZ5

**Accessory kits** Model(s) ZB6-YXXX+

**Accessory kits (16 mm line), "Class 9001"** Model(s) Z203, Z204, Z205, Z206, Z207, Z208, Z209, Z210, Z211, Z212, Z214, Z215, Z216

**Adapters** Model(s) LA7K0064

**Analogue joystick controllers** Model(s) XDALXXXXX+, XDAVXXXXX+

**AS-i safety interfaces** Model(s) ASISEA1C, ASISEK1C, ASISL4, ASISL5, ASISL1, ASISL2, ASISL4, ASISL5, ASISL5

**AS-interface fail safe monitors** Model(s) ASISAFEMON1, ASISAFEMON1B, ASISAFEMON2, ASISAFEMON2B

**Auxiliary Device Modular Tower Light, Accessory Light Unit** Model(s) XVUC29P

**Auxiliary Device Modular Tower Light, Terminal Block Unit** Model(s) XVUZ03, XVUZ04

**Auxiliary Device Modular Tower Light, Voice Unit** Model(s) XVUC9V, XVUC9VP

**Auxiliary Device Self Powered Switch and Receiver, Package** Model(s) XB4 R followed by F, M, G, E or C, followed by A, B, C or D, followed by two or three digits.

XB5 R followed by F, M, G, E or C, followed by A, B, C or D, followed by two or three digits.

**Auxiliary Device Self Powered Switch and Receiver, Rope Pull Switch** Model(s) ZBR P, followed by 1 or 2

**Auxiliary Device Enclosed** Model(s) XVUC43, XVUC44, XVUC45, XVUC46, XVUC47, XVUC48, XVUZ100T, XVUZ250T, XVUZ400T

**Auxiliary Device Enclosed Accessories for flush kit: Metal bezel, earthplates** Model(s) ZB4 BZ, followed by three digit number.

**Auxiliary Device Enclosed Accessory for XAR, ZARB devices** Model(s) ZARC followed by upto three digits

**Auxiliary Device Enclosed Boots (accessories)** Model(s) ZBD, ZBG, ZBP or ZB2-BP followed by any alphanumeric number.

**Auxiliary Device Enclosed Hand held Remote controller, Control panel base station** Model(s) ZARB followed by 12 or 18, followed by H or W. May be followed by M.

**Auxiliary Device Enclosed Hand held Remote controller, Package of Remote and Control panel base** Model(s) XAR followed by S or SK, followed by 8D, 8L or 12D, followed by 12W, 12H, 18W or 18H.

**Auxiliary Device Enclosed Hand held Remote controller, Remote** Model(s) ZART followed by 8D, 8L or 12D. May be followed by M.

**Auxiliary Device Enclosed Limit Switch** Model(s) XCR followed by A, B, E, or F, followed by 1 or 5, followed by 1, 2, 5, 7, or 8, may be followed by 1, may be followed by H7 or S, may be followed by up to five digits.

XCRT followed by 1 or 2, followed by 15, may be followed by H7 or S, may be followed by up to five digits.

**Auxiliary Device Enclosed Operators** Model(s) ZB4 - B, ZB5 - A or ZB5 - C, followed by A, B, C, D, F, G, H, J, K, L, P, R, S, T or X, followed by 1, 2, 3, 4, 5, 6, 7, 8 or 9, followed by one, two, three or four numbers, may be followed by M and/or 7.

**Auxiliary Device Enclosed Plastic bezel, plastic bezel label support, plastic brace., Cat. No.** Model(s) ZB5 AZ followed by three digit number.

**Auxiliary Device Open type** Model(s) XB5AS84449, XB5AS86449B4

**Auxiliary Device Open type Contact blocks** Model(s) ZBE, followed by 0, 1 or 2, followed by two digit number, may be followed by 6 or 6P, may be followed by 3, 5 or 9, may be followed by J

**Auxiliary Device Open type Hand held Remote controller, "Field bus Comm Analog card"** Model(s) ZARCFBA01

**Auxiliary Device Open type Hand held Remote controller, "Network communication card"** Model(s) ZARCIOT01

**Auxiliary Device Open type LED pilot light transcient voltage suppressors subunit** Model(s) ZBZ VG or ZBZ VM

**Auxiliary Device Open type Tower Light** Model(s) XVGU3SHAG, XVGU3SHAV, XVGU3SWG, XVGU3SWV

**Auxiliary contact blocks, open type** Model(s) LN1-DN11, LN1-DN116

**Auxiliary Devices, "Modular Tower Light, Accessory Flash Light Unit"** Model(s) XVUC63, XVUC64, XVUC65, XVUC66, XVUC67, XVUC68

**Auxiliary Devices, "Terminal Block Unit"** Model(s) XVUZ00

**Auxiliary devices** Model(s) LA4SKC1Y+, LA4SKE1Y+, XPSAXE5120C, XPSAXE5120P, XPSBCE3110C, XPSBCE3110P, XPSBCE3410C, XPSBCE3410P, XPSBCE3710C, XPSBCE3710P

**Auxiliary devices, limit switches** Model(s) XCMU21\*

**Auxiliary switch units, open type** Model(s) LA1-DC22, LA1-DC223, LA1-DC226, LAD-C22, LAD-C223, LAD-C226

**Auxillary Device: Modular Tower Light, Accessory Buzzer Unit** Model(s) XVUC9S, XVUC9SQ

**Auxillary Device: Modular Tower Light, Accessory Extender Unit** Model(s) XVUC020, XVUC020Q

**Auxillary Device: Modular Tower Light, Accessory Flexible Unit** Model(s) XVUZ06

**Auxillary Device: Modular Tower Light, Accessory Light Unit** Model(s) XVUC23, XVUC24, XVUC25, XVUC26, XVUC27, XVUC28, XVUC29

**Auxillary Device: Modular Tower Light, Power Unit** Model(s) XVUC21B, XVUC21BQ, XVUC21M, XVUC21MP, XVUC21MQP

**Auxillary Device: Modular Tower Light, Terminal Block Unit** Model(s) XVUZ01, XVUZ01Q, XVUZ02, XVUZ02Q, XVUZ05, XVUZ400, XVUZ800

**Base provided adapters** Model(s) LA7-D

**Beacons and indicating banks** Model(s) XVE, followed by C or L, followed by 2, 3, 5 or 6, may be followed by B, G or M, followed by one digit.

XVE-C, followed by 9 or 21, may be followed by B, G, M or P.

**Biometric switches** Model(s) XB5-S, followed by 1, 2, 3, 4 or 5, followed by B, followed by 2, followed by L with a number or followed by M12.

**Bodies for limit switches** Model(s) ZC, followed by D, P or T, followed by two numbers, may be followed by F, G, N or P, followed by two numbers.

ZCD followed by two numbers, may be followed by F, G, M, N or P, followed by two numbers.

ZCM-D followed by a two digit number, may be followed by C, L or M, followed by a one to five digit number.

ZCP followed by two numbers, may be followed by F, G, M, N or P, followed by two numbers.

ZCT followed by two numbers, may be followed by F, G, M, N or P, followed by two numbers.

**Button operators and contact blocks** Model(s) D1 or D2, followed by A2, A4 or A5, followed by B, G, R, S, W or Y, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

D1 or D2, followed by M, followed by 1 or 2, followed by Z, may be followed by three symbols, followed by DA11, DB11, -11F, -20F or DC22.

D1, D2, D3, D4 or D7, followed by A1, A3 or A6, followed by B, G, R, S, W or Y, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

D1, D2, D3, D4 or D7, followed by B1 or B2, followed by G, R, S or Y, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

D1, D2, D3, D4 or D7, followed by C1 or D1, followed by R or Y, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

D1, D2, D3, D4 or D7, followed by E1, followed by B, R or W, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

D1, D2, D3, D4 or D7, followed by F2, G2, G3, G4, G5, G6, H2, H3, H4, H5, H6 or H7, followed by R, S or Y, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

D1, D2, D3, D4 or D7, followed by L, followed by A, B, C, D, 1, 2, 3, 4, 5, 6, 7, 8 or 9, followed by 0, may be followed by three symbols, followed by DA01, -02, -10, -11, -20, DB01, -02, -10, -11, -11F, -20, -20F, DC04, -22, -40, DG01, -02, -10, -11 or -20.

**Cable entry supports** Model(s) ZC-DEFXX+, ZC-DEGXX+, ZC-DENXX+, ZC-DEPXX+, ZC-PEFXX+, ZC-PEGXX+, ZC-PENXX+, ZC-PEPXX+

**Cam-operated master switches** Model(s) XKBAXXXXX+, XKBEXXXXX+

**Coil suppressors** Model(s) LAD4, followed by D, V, RC or T, followed by 3, followed by B, E, G, N, R, S or U.

LAD4, followed by two or three letters and control wiring kits.

LAD4, followed by two or three letters and control wiring kits.

LAD4BB, may be followed by V and a letter.

**Connectors** Model(s) ZCM-CXXLXX+

**Contact blocks** Model(s) ZB2-BE-201 (h), ZB2-BE-202 (h), ZB2-BE101, ZB2-BE1016, ZB2-BE1019, ZB2-BE102, ZB2-BE1026, ZB2-BE1029, ZB6-E1B, ZB6-E1E, ZB6-E2B, ZB6-E2E, ZB6-Z1B, ZB6-Z1E, ZB6-Z2B, ZB6-Z2E

ZBE, followed by 1 or 2, followed by two numbers, may be followed by 6 or 6P, may be followed by 3, 5 or 9.

ZEN-L1111

**Contact blocks with or without pilot lights (16 mm line), "Class 9001"** Model(s) DU01, DU02, DU10, DU11, DU20, DUB01, DUB02, DUB10, DUB11, DUB20, DUF01, DUF02, DUF10, DUF11, DUF20, DUFB01, DUFB02, DUFB10, DUFB11, DUFB20, DUFR01, DUFR02, DUFR10, DUFR11, DUFR20

**Contact subunits** Model(s) ZB4-BZXXX+, ZB4-BZXXXX+, ZB5-AZXXX+, ZB5-AZXXXX+, ZBE501, ZBE5013, ZBE502, ZBE5023, ZBE503, ZBE5033, ZBE504, ZBE5043, ZBE505, ZBE5053, ZD4-PAXXX+, ZD5-PAXXX+, ZD6-PAXXX+

**Control stations** Model(s) XAL-D or XAL-K, followed by 1, 2, 3, 4 or 5, followed by a two digit number, may be followed by a letter and/or a number, followed by H7.

XAL-D01H7, XAL-D02H7, XAL-D03H7, XAL-D04H7, XAL-D05H7, XAL-K01H7, XAL-K02H7, XAL-K03H7, XAL-K04H7, XAL-K05H7

**Electromechanical output relays** Model(s) RE-7, followed by C, M, P, R, T or Y, followed by A, B, D, E, L, M, P, R, V or Y, followed by 11, 12 or 13, followed by BU or MW.

RE-8, followed by C, P, R, T or Y, followed by A, B, D, E, G, L or T, followed by 0, 1, 2, 3, 4 or 5, followed by 1 or 2, followed by B, F or Q, may be followed by U.

RM4J, followed by A, followed by 0 or 3, followed by 1 or 2, followed by B, F, M, Q or MW.

RM4L, followed by A or G, followed by 0 or 3, followed by 1 or 2, followed by B, F, M, Q or MW.

RM4T, followed by A, G, R or U, followed by 0, 2 or 3, followed by 0, 1, 2, 3, 4.

RM4U, followed by A or B, followed by 0 or 3, followed by 1, 2, 3, 4 or 5, may be followed by B, F, M, Q or MW.

**Enabling switches, grip type** Model(s) XY2-AU1, XY2-AU2

**Enclosures** Model(s) XAL-B or XAL-J, followed by 01, 02, 03, 04 or 05, followed by 1, followed by two numbers, may be followed by additional digits.

XAP-G or XAP-M, followed by two thru five numbers.

**Field additions** Model(s) D09906 (c), D09980 (c), D16906 (c), LA1-D04 (a), LA1-D10 (a), LA1-D11 (a), LA1-D1111 (a), LA1-D13 (a), LA1-D20 (a), LA1-D22 (a), LA2-D20 (a), LA2-D22 (a), LA2-D24 (a), LA3-D20 (a), LA3-D20A65 (a), LA3-D20H35 (a), LA3-D20H7 (a), LA3-D22 (a), LA3-D22A65 (a), LA3-D22H35 (a), LA3-D22H7 (a), LA3-D24 (a), LA3-D24A65 (a), LA3-D24H35 (a), LA3-D24H7 (a), LA4-K-A1F (b), LA4-K-A1U (b), LA4-K-C1B (b), LA4-K-C1E (b), LA4-K-E1B (b), LA4-K-E1E (b), LA4-K-E1FC (b), LA4-K-E1UG (b), LA4-K-KA1U (b), LA4-K-KC1B (b), LA4-K-KC1E (b), LA4-K-KE1B (b), LA4-K-KE1E (b), LA4-K-KE1FC (b), LA4-K-KE1UG (b), LA9D09982 (c), LA9D10 (c), LA9D101 (c), LA9D11 (c)

**Foot switches** Model(s) XPE, followed by B or G, followed by one, two or three alphanumeric digits.

**Illuminated operators** Model(s) ZB4-B, ZB5-A or ZB5-C, followed by A, B, C, D, G, H, J, K, L, P, R, S, T, X or W, followed by 1, 2, 3, 4, 5, 6, 7, 8 or 9, followed by one thru five numbers, may be followed by 3, may be followed by S, may be followed by M and/or 7.

**Illuminated push button subunits** Model(s) ZB4-BW0 or ZB5-AW0, followed by two thru five numbers and/or letters.

**Illuminated push buttons, full voltage type** Model(s) Z..BW06 (d), Z..BW06X+(d)

**Illuminated push buttons, resistor type** Model(s) Z..BW07 (d), Z..BW07X+(d)

**Illuminated push buttons, transformer type** Model(s) Z..BW01 (d), Z..BW02 (d), Z..BW03 (d), Z..BW04 (d), Z..BW94 (d), Z..BW95 (d), Z..BW98 (d)

**Illuminated push buttons/selector blocks** Model(s) ZB6, followed by Z, followed by B, G, H or M, followed by two numbers, followed by B or E.

**Indicating banks and beacons, enclosed type** Model(s) XVB followed by C followed by 9, 07 or 21, may be followed by B or M

XVB followed by C or L, followed by 0, 1, 2, 3, 4, 5, 6 or 8, may be followed by B, E, G or M, followed by one digit, may be followed by D.

XVD followed by B, G or M may be followed by 1 or 2, may be followed by S, may be followed by up to 8 digits included A, C, G, R or 6, may be followed by S and two digits.

XVD followed by C followed by 9, 07 or 21, may be followed by B or M

XVD followed by C or L, followed by 0, 1, 2, 3, 4, 5, 6 or 8, may be followed by B, E, G or M, followed by one digit, may be followed by D.

XVD followed by LS, followed by 3 or 6, may be followed by B, G or M, followed by one digit.

**Indicator bank adaptor AS-i units** Model(s) XVA-S102

**Indicator bank base unit AS-i units** Model(s) XVB-C21A

**Inductive proximity sensors AS-i units** Model(s) XS1-M30AS101, XS7-C40AS101, XS8-C40AS101

**Input indicators, open type, and coil suppressor kit modules for use with control circuit contactor types CA.D, LC.D or LP.D** Model(s) LA4-D, followed by a letter, followed by a letter or a number, may be followed by a letter.

LA9.D0998X+

**Interface modules** Model(s) ABR-2, followed by E or S, followed by 1, followed by 0 or 1, followed by 1, 2, 5 or 6, followed by B, E, F or M.

ABR-2EB312B, ABR-2SB312B

ABS-2, followed by EA, EC, SA or SC, followed by 01 or 02, followed by E or M, followed by A, B, E, F or M.

RMC, followed by A, L, N or V, followed by 2, 5 or 6, followed by 0, 1, 2 or 5, followed by BD.

RMPT-10BD, RMPT-13BD, RMPT-20BD, RMPT-23BD, RMPT-30BD, RMPT-33BD, RMPT-50BD, RMPT-53BD, RMPT-70BD, RMPT-73BD, RMT-J40BD, RMT-J60BD, RMT-J80BD, RMT-J90BD, RMT-K40BD, RMT-K60BD, RMT-K80BD, RMT-K90BD

**Interface relays** Model(s) ABR-1, followed by E or S, followed by 1, 3, 4 or 6, followed by 0 or 1, followed by 1, 2 or 8, followed by B, E, F, G or M.

XCK-N or XCN-R, followed by 21, 25, 26, 27, 28, 29, 01, 05, 06, 07, 08, 09, 31, 35, 37 or 39, followed by 02, 03, 06, 08, 10, 18, 21, 27, 39, 45 or 49, followed by P20, G11, F12 or P16, followed by blank or SXX (XX may be one or two digits).

**Joystick controllers** Model(s) XD2-GA, XD2-PA or XDL-PA, followed by two thru nine numbers.

XD4-PA or XD5-PA, followed by two numbers, may be followed by a letter.

**Joystick switches** Model(s) XD3-PAXX+

**Joystick switches, open type** Model(s) XDP-, followed by A, B, C or D, followed by four numbers, followed by C, followed by 1 or 2.

**Keypads AS-i units** Model(s) XBL-C5012F581, XBL-C5012R581

**LED beacons** Model(s) LRSC followed by -12 or -24, followed by R, Y, G or B, followed by -A.

LRX followed by -12 or -24, followed by R, Y, G or B, followed by -A.

XVR followed by 08 or 10, followed by B or J, followed by 03, 04, 05 and 06, may be followed by any letters (R, O, G, B or C).

**LED Beacons** Model(s) XVR08B03, XVR08B04, XVR08B05, XVR08B06, XVR08J03, XVR08J04, XVR08J05, XVR08J06, XVR10B03, XVR10B04, XVR10B05, XVR10B06, XVR10J03, XVR10J04, XVR10J05, XVR10J06

**LED mini sign towers** Model(s) LEU followed by T or G, followed by WB or blank, followed by -AC, may be followed by W, followed by -1 thru -5. LOU followed by T, followed by WB or blank, followed by -AC, may be followed by W, followed by -1 thru -5.

XVC followed by 4, followed by M, followed by 1 through 5, may be followed by 5, may be followed by S, may followed by T, may be followed by any letters(R, O, G, B or C).

XVC followed by 4, followed by M, followed by 1 thru 5, may be followed by 5, may be followed by S, followed by T or blank, may be followed by any letters (R, O, G, B or C).

XVC followed by 6, followed by M, followed by 1 through 5, may be followed by 5, may be followed by S, may be followed by K, may be followed by T, may be followed by any letters (R, O, G, B or C).

XVC4M1, XVC4M15S, XVC4M2, XVC4M25S, XVC4M3, XVC4M35S, XVC4M4, XVC4M45S, XVC4M5, XVC4M55S, XVC6M1, XVC6M15S, XVC6M15SK, XVC6M1K, XVC6M2, XVC6M25S, XVC6M25SK, XVC6M2K, XVC6M3, XVC6M35S, XVC6M35SK, XVC6M3K, XVC6M4, XVC6M45S, XVC6M45SK, XVC6M4K, XVC6M5, XVC6M55S, XVC6M55SK, XVC6M5K

**LED rotating light beacons** Model(s) LRLK may be followed by B, followed by -12 or -24, followed by R, Y, G or B, followed by -A.

LRMT followed by -12, -24, -120 or -230, followed by B, G, R or Y, followed by -A, may be followed by L.

XVR followed by 12, followed by B or J, followed by 03, 04, 05 and 06, may be followed by S, may be followed by any letters (R, O, G, B or C).

XVR followed by 13 followed by B, J, G or M, followed by 03, 04, 05 and 06, may be followed by L, may be followed by any letters (R, O, G, B or C).

XVR12B03, XVR12B03S, XVR12B04, XVR12B04S, XVR12B05, XVR12B05S, XVR12B06, XVR12B06S, XVR12J03, XVR12J03S, XVR12J04, XVR12J04S, XVR12J05, XVR12J05S, XVR12J06, XVR12J06S, XVR13B03, XVR13B03L, XVR13B04, XVR13B04L, XVR13B05, XVR13B05L, XVR13B06, XVR13B06L, XVR13G03L, XVR13G04L, XVR13G05L, XVR13G06L, XVR13J03, XVR13J04, XVR13J05, XVR13J06, XVR13M03L, XVR13M04L, XVR13M05L, XVR13M06L

**LED sign towers** Model(s) UTL followed by B or blank, followed by -AC, followed by W or blank, followed by -1 thru -5.

XVC followed by 1, followed by M, followed by 1 through 5, may be followed by K or SK, may be followed by any letters (R, O, G, B or C).

XVC1M1K, XVC1M1SK, XVC1M2K, XVC1M2SK, XVC1M3K, XVC1M3SK, XVC1M4K, XVC1M4SK, XVC1M5K, XVC1M5SK

**LED tower lights** Model(s) UTL may be followed by B, followed by -24, followed by -1 thru -5.

XVC followed by 1, followed by B, followed by 1 through 5, may be followed by S, followed by K, may be followed by T, may be followed by any letters (R, O, G, B or C).

XVC1B1K, XVC1B1KT, XVC1B1SK, XVC1B1SKT, XVC1B2K, XVC1B2KT, XVC1B2SK, XVC1B2SKT, XVC1B3K, XVC1B3KT, XVC1B3SK, XVC1B3SKT, XVC1B4K, XVC1B4KT, XVC1B4SK, XVC1B4SKT, XVC1B5K, XVC1B5KT, XVC1B5SK, XVC1B5SKT

**Limit switches** Model(s) XCD-R followed by D, P or T, followed by four numbers, followed by F, G, M, N or P, followed by two digit number may be followed by a suffix of letter and/or number up to 3 digits.

XCK-D followed by D, P or T, followed by four numbers, followed by F, G, M, N or P, followed by two digit number may be followed by a suffix of letter and/or number up to 3 digits.

XCK-J, XCL-J, ZCK-J or ZCK-JD, followed by 1 thru 9, may be followed by one thru four numbers, may be followed by A, H7, H29 or D.

XCK-P followed by D, P or T, followed by four numbers, followed by F, G, M, N or P, followed by two digit number may be followed by a suffix of letter and/or number up to 3 digits.

XCK-S followed by 1 to 9, followed by two numbers, may be followed by H7 or H29, may be followed by S followed by a suffix of letter or/and number of two digits

XCK-SD followed by 1 to 9, followed by two numbers, may be followed by H7 or H29, may be followed by S followed by a suffix of letter or/and number of two digits

XCK-T followed by D, P or T, followed by four numbers, followed by F, G, M, N or P, followed by two digit number may be followed by a suffix of letter and/or number up to 3 digits.

XCKVR followed by a two digit number, followed by D or SR, followed by 1 or 2, followed by H29 or H7.

XCN-T or XCN-TR, followed by 21, 25, 27, 29, followed by 02, 03, 06, 08, 10, 18, 21, 27, 39, 45 or 49, followed by P16, or G11, followed by blank or SXX (XX may be one or two digits).

XCP-R followed by D, P or T, followed by four numbers, followed by F, G, M, N or P, followed by two digit number may be followed by a suffix of letter and/or number up to 3 digits.

XCT-R followed by D, P or T, followed by four numbers, followed by F, G, M, N or P, followed by two digit number may be followed by a suffix of letter and/or number up to 3 digits.

ZCK-S followed by 1 to 9, followed by two numbers, may be followed by H7 or H29, may be followed by S followed by a suffix of letter or/and number of two digits

ZCK-SD followed by 1 to 9, followed by two numbers, may be followed by H7 or H29, may be followed by S followed by a suffix of letter or/and number of two digits

**Limit switches for interlocking** Model(s) XCS, followed by LF or LE, followed by six numbers, followed by 2 or 3, may be followed by two numbers.

**Limit switches for safety applications** Model(s) XCK.J59, XCK.J69 or XCK.J79, followed by a number, followed by 0, 2, 3 or 4, may be followed by 2.

XCS-A, XCS-B, XCS-C or XCS-E, followed by three thru seven numbers.

XCS-D, XCS-DDR, XCS-P or XCS-PPR, followed by four numbers, followed by F, G, M, N or P, followed by two numbers.

XCS-TEXXXX+

**Limit switches, cable entry supports** Model(s) ZC, followed by DE or PE, followed by F, G, N or P, followed by a two digit number.

**Low voltage intelligent motor protection relays** Model(s) LR97D followed by 015, 07, 25 or 38, followed by B, E, F7 or M7.

LT47 followed by 06, 30 or 60, followed by B, E, F7 or M7, followed by S or A.

**Machine operated switches, enclosed type** Model(s) XC2-JC\*, XC2-JD\*, XCK-L (e), XCK-M (e), XCK-ML (e), XCK-MR (e), ZCK-J11 (e), ZCK-J21 (e), ZCK-J41 (e), ZCK-L (e), ZCK-LD (e), ZCK-M (e), ZCK-MD (e), ZCK-ML (e)

**Magnetically operated auxiliary contacts, AC and DC coil devices** Model(s) CAD, followed by two numbers, may be followed by a number, followed by one or two letters, may be followed by a number and may be followed by S207 or S335

**Magnetically operated control switches** Model(s) CA2-DK22 or CA3-DK22, may be followed by 6, may be followed by a letter.

CA2-DN or CA4-DN, followed by two numbers, may be followed by 6, may be followed by a letter.

CA2-KN, followed by two or three number, may be followed by one or two letters and one or two numbers.

Cat. Nos. CAK, followed by a 2 or 3 digit number, followed by two letters, maybe followed by S207 or S335.

Cat. Nos. CAK, followed by a 2 or 3 digit number, followed by two letters, maybe followed by S335

Cat. Nos. CAK, followed by a 2 or 3 digit number, followed by two letters, maybe followed by S335.

**Manually operated emergency stop switches** Model(s) XY2-CE followed by 1 thru 7 or F, G, J or K, followed by A or C, followed by three numbers, followed by H7 or H7TK.

**Mechanical latches, open type** Model(s) LA6-DK, followed by a number, may be followed by 6, followed by one or two letters.

LAD6K10, may be followed by 6, followed by one or two letters.

**Miniature limit switches** Model(s) XCM-D followed by a four or five digit number, followed by C, L, or M followed by a one or two digit number, may be followed by up to 4 alphanumeric characters.

XCM-N followed by a four or five digit number, followed by C, L, or M followed by a one or two digit number, may be followed by up to 4 alphanumeric characters.

XCS-M followed by a four or five digit number, followed by C, L, or M followed by a one or two digit number, may be followed by up to 4 alphanumeric characters.

**MOV, Diode and LED socket modules** Model(s) RUW240BD, RUW241P7, RUW242B7, RUW242P7, RXM021BN, RXM021FP, RXM021RB, RXM040W, RXM041BN7, RXM041FU7

**Multifunction motor protection relays** Model(s) LT6POM005FM, LT6POM025FM

**Operating heads** Model(s) ZB6, followed by A, C or D, followed by a letter, followed by a number or a letter, may be followed by 1 thru 7.

ZB6-ASXXX+

**Operating heads for limit switches** Model(s) Cat. No. ZCE (+)

**Operator modules** Model(s) GC2DSP

**Operators** Model(s) ZB4-B, ZB5-A or ZB5-C, followed by A, B, C, D, G, H, J, K, L, P, R, S, T or X, followed by one thru four numbers, may be followed by M.

ZD4-PAXX+, ZD5-PAXX+

**Operators (16 mm line), "Class 9001"** Model(s) D5, D6, D8 or D9, followed by A, B, C, E, G, L, R or V, followed by a number, followed by a letter.

**Overload relay adaptors for use with overload relay** Model(s) LA7 D followed by 1064, 2064, 3058 or 3064

LR2/LR3 D1 followed by 1064, 2064, 3058 or 3064

LR2/LR3 D2 followed by 1064, 2064, 3058 or 3064

LR2/LR3 D3 followed by 1064, 2064, 3058 or 3064

LR2/LR3 D4 followed by 1064, 2064, 3058 or 3064

**Overload relays** Model(s) LR, followed by 1, 3 or 4, followed by D, followed by 09, 12, 16, 25, 40, 63 or 80, followed by three numbers, may be followed by A65, when used with contactors LC1-D or LP1-D or adaptors LA7-D09 followed by 54 or 64, may be followed by A60 or A65 .

LR3D3, followed by two numbers, may be followed by one letter, may be followed by 3 or 6.

**Pendant stations** Model(s) XAC, followed by A, followed by 20 or 21, followed by 1, 3, 5, or 7, may be followed by 3 or 4.

XAC.A, followed by a one or two numbers, followed by 71, 81, 91 or may be followed by a combination of s and D (up to three letters), may be followed by 3, 4 or 5, may be followed by one digit, followed by H7.

XAC.A02H7, XAC.A03H7, XAC.A04H7, XAC.A05H7, XAC.A06H7, XAC.A08H7, XAC.A12H7

**Photoelectric detectors AS-i units** Model(s) XUJ-K063539AS (f), XUJ-K103534AS (f), XUJ-K123538AS (f), XUJ-K703538AS (f)

**Photoelectric sensors** Model(s) XUE or XUR, followed by A, F, H, J or T, followed by five or six numbers, may be followed by H7.

XUR, followed by H, followed by five numbers, may be followed by H7.

**Photoelectric switches** Model(s) XUJ, followed by B, K, LM or M, followed by four to six numbers, may be followed by D, H or P, followed by a number.

**Pilot devices, open type** Model(s) XB2-M, followed by A, B, C, D, E, G, H, J, K, L, P, Q, R, S, T, V, W, X or Y, followed by numbers.

**Pilot light blocks** Model(s) ZAL-V followed by B, G, or M, followed by 1, 3, 4, 5 or 6.

ZAL-V18 followed by B, BG, G, J or M, followed by one digit.

ZB6 followed by E or Z, followed by B, G, H or M, followed by one digit, followed by B.

ZBV followed by B, BG, G, J or M, followed by one digit, may be followed by 3, 5, 9 or S

ZBV-18 followed by B, BG, G, J or M, followed by one digit, may be followed by 3, 5, 9 or S

ZBV-6 followed by one digit, may be followed by 3, 5 or 9.

**Pilot light blocks (16 mm line), "Class 9001"** Model(s) DUF, DUFB

**Pilot light heads** Model(s) ZB4-BV0, ZB5-AV0 or ZB5-CV0, followed by one or two numbers, may be followed by S.

**Pilot light subunits** Model(s) ZB4-BV or ZB5-AV, followed by one thru four number and/or letter suffixes.

**Pilot lights** Model(s) D1, D2, D3, D4 or D7, followed by V1 or V2, followed by B, G, O, R, W or Y, may be followed by three symbols, followed by DFGN, DFSN, DTEA, DTGB thru DTGH, DTGP, DTGL, DTGR, DTSA thru DTSH, DTSK, DTSL, DTSP or DTSR.

XB5-E, followed by V, followed by B, G or M, followed by a number, may be followed by 3.

**Pilot lights, flashing type** Model(s) Z..BV181 (g), Z..BV184 (g), Z..BV191 (g), Z..BV194 (g)

**Pilot lights, full voltage type** Model(s) XVA, followed by C or L, followed by 3 or 4, followed by 3 thru 8, may be followed by 1.

XVA, followed by C or L, followed by 6 or 7, followed 3 thru 7, followed by B or C, followed by three or four number.

XVA, followed by LC or LD, followed by 3 or 4, followed by 3 thru 8, may be followed by B120.

Z..BV68X+(g), Z..BV6X+(g)

ZB2-BV006X+ (for use with Pendant station XAC-A)

**Pilot lights, resistor type** Model(s) Z..BV7X+(g)

**Pilot lights, transformer type** Model(s) Z..BV1X+(g), Z..BV2X+(g), Z..BV3X+(g), Z..BV4X+(g), Z..BV94X+(g), Z..BV95X+(g), Z..BV98X+(g)

**Proximity switches** Model(s) XCS followed by ZC, ZP or ZR, followed by 5 or 7, followed by 0 or 9, followed by 0 or 1, followed by 1, 2 or 5, may be followed by 0, may be followed by LxxM8 or LxxM12.

XSD, followed by A40, A50, A60, C40, C60, H40, H60, J40, J60, M40, M60 or T2, followed by numbers or may be followed by a letter.

**Push button control stations AS-i units** Model(s) XAL-S2001, XAL-S2002, XAL-S2003

**Push button pilots and push-on/off pilots** Model(s) D1, D2, D3 or D4, followed by Y1, Y2 or Y3, followed by B, G, O, R, W or Y, may be followed by three symbols, followed by DFGN, DFSN, DKSM, DTGN, DTGR, DTSA through DTSH, DTSK, DTSL, DTSP, DTSR or DWSM, followed by 11, 22 or R1.

**Push buttons and pilot light assemblies (22 mm line)** Model(s) XB4-B followed by A, C, D, G, H, J, K, L, P, R, S, T, V, W or X, followed by two thru five or Six numbers and/or letters.

XB5-A followed by A, C, D, G, H, J, K, L, P, R, S, T, V, W or X, followed by two thru five or Six numbers and/or letters.

**Push buttons and pilot lights (16 mm line)** Model(s) XB6, followed by A, C or D, followed by A, D, E, F, G, K, S, V or W, followed by three or four numbers and/or letters, may be followed by a letter.

**Push buttons, selector switches and illuminated push buttons** Model(s) XB7-N followed by A, D, G, H, J, L or W, followed by two, four or five numbers, may be followed by B, G or M, may be followed by 1 or 2.

**Push buttons, selector switches, emergency stop switches, pilot lights and illuminated push buttons,** Model(s) XB7-E, followed by A, H, D, G, S, V or W, followed by two thru four numbers, may be followed by B, G or M, may be followed by 1 or 2, may be followed by P, may be followed by S or 3.

**Safety interlock switches** Model(s) XCS-PAXXX+, XCS-PLXXX+, XCS-PRXXX+, XCS-TAXXX+, XCS-TLXXX+, XCS-TRXXX+

**Safety modules , "Series Preventa"** Model(s) XPS-MC, followed by two numbers, followed by X or Z, may be followed by C or P.

**Safety relays, "Series Preventa"** Model(s) XPS-AL, -AM, -AMF, -AP, -APF, -AR, -AS, -ASF, -AT, -ATE, -AV, -AX, -BA, -BC, -CEN, -CEP, -DA, -ECM, -ECP, -FB, -NS, -OT, -PVK, -PVT, -TSA, -TSW or -VN, followed by four or five numbers, may be followed by Z, may be followed by T, followed by three numbers.

**Safety relays** Model(s) XPS-AF, -AFL, -AK, -AV, -MP, -AC, -AR, -ATE, -TSA, -TSW, -DMB, -DME, -BF, -VC, -VNE or -CM, followed by four thru six numbers, may be followed by P, may be followed by T, with or without three numbers.

**Safety switches** Model(s) XCS-MP50L\*, XCS-MP59L\*, XCS-MP70L\*, XCS-MP79L\*, XCS-MP80L\*, XCS-MP89L\*

**Selector cam switches** Model(s) XB3-D, followed by five numbers, followed by C, M or S, followed by two or three numbers.

**Self powered receivers** Model(s) XB5 RFB01, ZBR RC, ZBR RD

**Self Powered Switch and Receiver, Antenna** Model(s) ZBRA2

**Self Powered Switch and Receiver,Access Point** Model(s) ZBRN2

**Self Powered Switch and Receiver,Access Point** Model(s) ZBRN1

**Self Powered Switch and Receiver,Ethernet protocol module** Model(s) ZBRCETH

**Self powered switches and receivers, handy boxes** Model(s) ZBR M followed by three, four or five digits, followed by two digits, for use with transmitter components Pushbutton, ZBR4R or ZBR5R series

**Self powered switches and receivers, relay-antennae** Model(s) ZBR A1

**Self powered switches and receivers, transmitters** Model(s) ZBR T1, ZBR T2, ZBR TP

**Single digit displays** Model(s) ZA2-VAXX+

**Solid state output relays** Model(s) RE-9, followed by M, R or T, followed by A or S, followed by 1, 2, 3 or 5, followed by 1, followed by MW, may be followed by 7.

**Switch units, open type** Model(s) LA1-DC22, LA1-DC226

LA1-DN or LA8-DN, followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6, may be followed by 5040.

**Switches with interlocking electromagnets** Model(s) XCK.J59 or XCK.J79, followed by 2, 3, 4, 5, 6 or 8, followed by a number, followed by B, E, F, J or M, followed by 0, 2, 3 or 4, followed by 1, 1H7 or 2.

XCS-L5 or XCS-L7, followed by 0, 2, 4, 5, 6, 8 or X, followed by a number or X, followed by B, E, F, J or M, followed by 1, 2, 3 or 4.

**Terminal kits** Model(s) XPS-MCTCXX+, XPS-MCTSXX+



**Test output units** Model(s) ZB-.V156, ZB-.VB.156, ZBZ-.156

**Thermal overload relays** Model(s) LR-D15XX+, LR-D15XX6+, LR1-D32353, LR2D3321A66, LR2K-0301, LR2K-0302, LR2K-0303, LR2K-0304, LR2K-0305, LR2K-0306, LR2K-0307, LR2K-0308, LR2K-0310, LR2K-0312, LR2K-0314, LR2K-0316

LR3D3 or LRD3, followed by two numbers, may be followed by L, may be followed by 3 or 6.

LRD-33, LRD-43, LR2-D13, -D15, -D23, -D25, -D33, -D35, -D43, LR3-D13, -D15, -D23, -D25, -D33, -D35 or -D43, followed by two numbers, may be followed by 6 or S165, may be followed by A1.

**Thermal overload relays, adapters** Model(s) LAD7B106

**Thermistor protection units for operation with PTC (Positive Temperature Coefficient) thermistor probe** Model(s) LT3 followed by SEOO, or SAOO, or SMOO, followed by one or two letters.

**Timers** Model(s) LAD T0, LAD T03, LAD T06, LAD T4, LAD T43, LAD T46, LAD-R2, LAD-R23, LAD-R26, LAD-R4, LAD-R43, LAD-R46, LAD-RO, LAD-RO3, LAD-RO6, LAD-S2, LAD-S23, LAD-S26, LAD-T2, LAD-T23, LAD-T26

**Top-adder auxiliary switch blocks, open type** Model(s) LA1-KN, followed by two or three numbers, may be followed by 7, M or P.

**Tower Light, "Series XVGU"** Model(s) XVGU3SHAG, XVGU3SHAV, XVGU3SWG, XVGU3SWV

**Transformers for illuminated pushbuttons** Model(s) ZB-W3, ZB-W4, ZB-W5, ZB-W8, ZB-W9

**Transformers for pilot lights** Model(s) ZB-V3, ZB-V4, ZB-V5, ZB-V8, ZB-V9, ZBV5B, ZBV8B, ZBV9B

**Transient suppressors** Model(s) LA4SKC1U, LA4SKE1E, LA4SKE1U

**Trip wire switches** Model(s) XY2CH, followed by 1 or 3, followed by 1, 2, 3, or 4, followed by 0, 1, 2, 3, 4, 5, 6 or 9, followed by 1, 5, 7 or 9, followed by 0, followed by H7, may be followed by TK.

Model(s) Wall mounting support Model(s) XVUZ12

## Investigated to ANSI/UL 60947-1 and ANSI/UL 60947-4-1

**Adapter** Model(s) LAD7B10 may be followed by S183 and wiring kits Cat. No. LAD7C1 and LAD7C2

**Adapter base** Model(s) LA7-D

**Ambient compensated and differential electronic thermal overload relays** Model(s) LR9D followed by two or four digit numbers, LR9F

**Ambient compensated and differential thermal overload relays** Model(s) LR3D3 followed by two digit numbers may be followed by a L or blank, may be followed by 3 or 6

LRD3

**Auxiliary Devices** Model(s) LR3-D35 followed by two digit numbers, may be followed by 6

**Coil suppressors** Model(s) LAD4BB may be followed by V and a letter

**Contacting Mounting Adaptor** Model(s) LA7-D4054 may be followed by A65

**Low voltage intelligent motor protection relays, "Type TeSys T"** Model(s) LTMEV40 may be followed by 08, 27 or 100, may be followed by M, P, D, C or E, followed by BD or FM. Filter LTM9F for use with TeSys T

LTMR may be followed by 08, 27 or 100, may be followed by M, P, D, C or E, followed by BD or FM. Filter LTM9F for use with TeSys T

**Low voltage intelligent motor protection relays** Model(s) LR97D followed by 015, 07, 25 or 38, followed by B, E, F7 or M7

LT47 followed by 06, 30 or 60, followed by B, E, F7 or M7, followed by S or A

**Low voltage intelligent motor protection relays, filters** Model(s) LTM9F (Dedicated for TeSys T)

**Multifunction Motor Protection Relay** Model(s) LT6 followed by POM005FM or POM025FM

**Overload Relay** Model(s) LA7-D09 followed by 54 or 64 followed or not by A60 or A65

**Overload relay adaptors for use with overload relay** Model(s) LR2-D1, LR2-D2, LR2-D3, LR2-D4, LR3-D1, LR3-D2, LR3-D3, LR3-D4

**Thermal overload relay** Model(s) LR2-D25 followed by two digit numbers, may be followed by 6. Adapter base, Cat. No. LA7-D

LR2-D35 followed by two digit numbers, may be followed by 6

**Thermal overload relays** Model(s) LR-D15 followed by two digit numbers, may be followed by 6 or S165, may be followed by A1

LR1 followed by 40, 63, 80 followed by three digit numbers may or may not be followed by A65

LR1-09 followed by three digit numbers followed or not by A65

LR1-12 followed by three digit numbers followed or not by A65

LR1-16 followed by three digit numbers followed or not by A65

LR1-25 followed by three digit numbers followed or not by A65

LR1-D followed by 32, followed by three digit numbers followed by A65

LR2 D33 followed by two digit numbers may be followed by 6 or by A66

LR2 D43 followed by two digit numbers may be followed by 6 or by A66

LR2-D13 followed by two digit numbers, may be followed by 6

LR2-D15 followed by two digit numbers, may be followed by 6 or S165, may be followed by A1

LR2-D23 followed by two numbers, may be followed by 6

LR2K followed by -0301, -0302, -0303, -0304, -0305, -0306, -0307, -0308, -0310, -0312, -0314, -0316

LR3 D33 followed by two digit numbers may be followed by 6 or by A66

LR3 D43 followed by two digit numbers may be followed by 6 or by A66

LR3 followed by 09, 12, 16 and 25 followed by three digit numbers followed or not by A65

LR3-D followed by 40, 63, 80 followed by three digit numbers may or may not be followed by A65

LR3-D-32 followed by three digit numbers followed by A65

LR3-D13 followed by two digit numbers, may be followed by 6

LR3-D15 followed by two digit numbers, may be followed by 6 or S165, may be followed by A1

LR3-D23 followed by two numbers, may be followed by 6

LR3-D25 followed by two digit numbers, may be followed by 6

LR4-D followed by 09, 12, 16 and 25 followed by three digit numbers followed or not by A65

LRD 33 followed by two digit numbers may be followed by 6 or by A66

LRD 43 followed by two digit numbers may be followed by 6 or by A66

LRD followed by two digit numbers followed by L, may be followed by one digit number, may be followed by S183

**Thermal overload relays, adapters** Model(s) LAD7B106 may be followed by S183(#)

LAD7B205 may be followed by S183 and NEMA adapter 9065SAD75

**Thermal overload relays, wiring kits** Model(s) LAD7C1(#), LAD7C2(#)

Model(s) LA7 D followed by 1064, 2064, 3058 or 3064

## Investigated to ANSI/UL 60947-1 and ANSI/UL 60947-5-1

**Accessories: Illuminated rings for pushbuttons** Model(s) Cat. No. ZBY9W followed by one digit, , followed by B, G or M, followed by three or four digits.

**Auxiliary Device Open type** Model(s) DPEAN followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6 or 3, may be followed by 5040, may be followed by S (for LADN22 only)

LA1-DC followed by 22, may be followed by 6 or 3

LA1-DN followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6 or 3, may be followed by 5040, may be followed by S (for LADN22 only)

LA8DN followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6 or 3, may be followed by 5040, may be followed by S (for LADN22 only)

LAD-8N followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6 or 3, may be followed by 5040, may be followed by S (for LADN22 only)

LAD-C followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6 or 3, may be followed by 5040, may be followed by S (for LADN22 only)

LAD-N followed by 01, 02, 04, 10, 11, 13, 20, 22, 31 or 40, may be followed by 6 or 3, may be followed by 5040, may be followed by S (for LADN22 only)

**Auxiliary contactors** Model(s) CAD ac coil devices, followed by two digit numbers may be followed by one digit number, followed by one or two letters, may be followed by a digit number and maybe followed by S335

**Auxiliary contacts** Model(s) CAD dc coil devices followed by two digit numbers may be followed by one digit number, followed by one or two letters, may be followed by a digit number and maybe followed by S207

**Auxiliary Devices** Model(s) CA2-DN122 with or without Nos. -9, A60, -A65, with or without No. H7

CA2-DN131 with or without Nos. -9, A60, -A65, with or without No. H7

CA2-DN140 with or without Nos. -9, A60, -A65, with or without No. H7

CA3 DN followed by two digits, may be followed by \*6, may be followed by a suffix letter

CA3-DK22 may be followed by a suffix letter may be followed by a suffix letter

GV4ADM1111

**Auxiliary devices** Model(s) LA1SK02, LA1SK11, LA1SK20, LA4SKC1 followed by a letter, LA4SKE1 followed by a letter

**Auxiliary switch contact blocks, open type** Model(s) LA1-DX followed by a two digit number, \*may be followed by 6

LA1-DY followed by a two digit number, \*may be followed by 6

LA1-DZ followed by a two digit number, \*may be followed by 6

**Auxiliary switch units** Model(s) LA1-KN followed by a 2 or 3 digit number, may be followed by 7, M or P

**Coil suppressors** Model(s) LAD4 followed by two or three letters and control wiring kits

**Control relays** Model(s) CA2SK followed by 11 or 20, followed by a letter, followed by a digit number or a letter

CA3SK followed by 11 or 20, followed by a letter, followed by a digit number or a letter

**Control Station** Model(s) Cat. No. XAL-D or -K , may be followed by W, followed by 01, 02, 03, 04 or 05, followed by H7.

**Control switches** Model(s) CA2-DK22 may be followed by a suffix letter may be followed by a suffix letter

CA2-DN followed by two digits, may be followed by \*6, may be followed by a suffix letter

CA2-KN followed by a 2 or 3 digit number may be followed by one or two letters and a one or two digit number

LA4-K followed by E1B, E1E, E1UG, C1B, C1E, A1U, A1F, or E1FC

**Industrial control relay with mechanically interlocked, alternating contacts** Model(s) CA2SKE20

**input indicator and coil suppressor kit modules** Model(s) LA4-D followed by a letter, followed by a letter or digit number, followed or not by a letter

**Input indicator and coil suppressor kit modules** Model(s) LA9-D0998 followed by two digits, may be followed by \*6, may be followed by a suffix letter

**Magnetic Motor Controllers** Model(s) LA2-D20 may or may not be followed by H7, A65, or H35

LA2-D22 may or may not be followed by H7, A65, or H35

LA2-D24 may or may not be followed by H7, A65, or H35

LA3-D20 may or may not be followed by H7, A65, or H35

LA3-D22 may or may not be followed by H7, A65, or H35

LA3-D24 may or may not be followed by H7, A65, or H35

**Magnetic motor controllers or auxiliary devices** Model(s) LA1-D followed by 04, 10, 11, 13, 20, 22, 40 or 1111, may or may not be followed by H7, A65 or H35

**Magnetically operated control switches** Model(s) CA3-KN

CA4-KN followed by a 2 or 3 digit number, may be followed by one or two letters and one or two digit numbers

CAK followed by a 2 or 3 digit number, followed by one letters and one digit numbers, maybe followed by S335

CAK followed by a 2 or 3 digit number, followed by two letters, maybe followed by S207 or S335

**Mechanical Latching Mechanisms** Model(s) LA6-DK followed by a number, may be followed by 6, followed by one or two letters

LAD6K10 may be followed by a suffix letter may be followed by a suffix letter

**Operator modules** Model(s) GC2DSP, LTMCU, LTMUCUC, LTMCUF

**Plug-in devices** Model(s) LAD4-D followed by 3, followed by B, E, S, G, U, R, or N

LAD4-RC followed by 3, followed by B, E, S, G, U, R, or N

LAD4-T followed by 3, followed by B, E, S, G, U, R, or N

LAD4-V followed by 3, followed by B, E, S, G, U, R, or N

**Thermistor protection units for operation with PTC (Positive Temperature Coefficient) thermistor probe** Model(s) LT3 followed by SE00, or SA00, or SM00, followed by one or two letters

**Timer** Model(s) LAD-R0 may be followed by 6 or 3, LAD-T0 may be followed by 6 or 3, LAD-T4 may be followed by 6 or 3

**Timers** Model(s) LAD-R2 may be followed by 6 or 3, LAD-R4 may be followed by 6 or 3, LAD-S2 may be followed by 6 or 3, LAD-T2 may be followed by 6 or 3

## Investigated to

**Adapters** Model(s) 9065SAD75

**Open type, Thermal overload relays with ambient compensation** Model(s) LR3D followed by two digit numbers may be followed by one digit number, may be followed by S183(#)

LRD followed by two digit numbers may be followed by one digit number, may be followed by S183 (#)

**Thermal overload relays** Model(s) LR3D followed by two digit numbers followed by L,

# - Investigated to ANSI/UL 60947-1, ANSI/UL 60947-4-1A, CAN/CSA-C22.2 No. 60947-1 and CAN/CSA-C22.2 No. 60947-4-1A

(a) - May be factory or field installed on the CA2-D, CA3-D devices.

(b) - May be factory or field installed on the CA2KN or CA3KN devices.

(c) - May be factory or field installed on the LC1-D, LC2-D or LE1-D devices.

(d) - These illuminated units are intended to be used in XA2.B, XB2.B, XB3.B illuminated push button and illuminated selector switch Series.

(e) - Followed by alpha numeric digits, may be followed by H7 or H29.

(f) - Provided with the back cover adaptor XUJ-ZAS1.

(g) - These pilot light units are to be used in XA2.B, XB2.B, XB3.B Series.

(h) - Models are for use in XA2-B, XB2-B, XB3-B, push buttons and selector switches.

\* - May be followed by additional numbers and letters.

+ - followed by a two or three digit or alphanumeric number

[Click here to view the Colombia Market Access Certification](#)

Last Updated on 2019-04-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

