

Compression Splice VERSAtile™ Minimum Tension

by ANDERSON
Catalog ID: VHS350

Copper long barrel Versatile splice, LNG BARREL 350MCM

- For use with VersaCrimp or conventional die type tooling.



* Representative image

Product Details

General

Application	Power Connector
Color Code	Red
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	VC6-3, VC6FT, VC7, VC7FT
Inhibitor Loaded	No
Material	Copper
Tension Range	0 lb
Trade Name	NO
UPC	096359338932
UPC 12 Digit	096359338932

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Dimension - L Length Overall mm	0 mm
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	4.12 in
Weight	0.294 lb

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600

Conductor Related

Conductor Diameter (Conventional Tooling) - Maximum	0.675 in
Conductor Diameter (Conventional Tooling) - Minimum	0.675 in
Conductor Diameter (VersaCrimp) - Maximum	0.675 in
Conductor Diameter (VersaCrimp) - Minimum	0.464 in
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications and Compliance

Certification - CSA Approved	Y
Certification - ETL	N
Certification - UL Recognized	N
Certification - cULus	N
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Carton Quantity	18 EA
Pallet Quantity	3000 EA

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
 210 N. Allen Centralia, MO 65240 USA
 Phone: (573) 682-5521
 Fax: (573) 682-8475
 Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
 Fax: +1-573-682-8516
 Email: hpsintlcs@hubbell.com