



[Catalog Home](#)



**Product Datasheet** **ANDERSON FARGO**

**VHSS2 -- Versatile Splice**



Copper short barrel Versatile splice

**Product Specifications**

|   |   |
|---|---|
| <p><b>Splice Type</b></p>                                 |  <p><b>VERSAtile™</b><br/><b>Compression Splices</b><br/>(For use with Die type<br/>and VersaCrimp tools)</p>                          |
| <p><b>Versatile Compression Series</b></p>                |  <p><b>VHSS Series</b><br/><b>Compression Splice</b><br/><b>VERSAtile™</b><br/><b>Minimum Tension</b><br/><b>Copper Conductor</b></p> |
| <p><b>PDF Catalog Page</b></p>                            | <p><a href="#">Click HERE to view the web page.</a></p>   |
| <p><b>Conventional Tooling Conductor Size Minimum</b></p> | <p>0.292 in</p>   |
| <p><b>Conventional Tooling Conductor Size Maximum</b></p> | <p>0.292 in</p>   |
| <p><b>VersaCrimp Conductor Size Minimum</b></p>           | <p>0.184 in</p>   |
| <p><b>VersaCrimp Conductor Size Maximum</b></p>           | <p>0.292 in</p>   |
| <p><b>Material</b></p>                                    | <p>Copper</p>   |
| <p><b>Conventional Tooling Minimum Conductor</b></p>      | <p>.292 in</p>  |
| <p><b>Conventional Tooling Maximum Conductor</b></p>      | <p>.292 in</p>  |
| <p><b>Conventional Tooling Conductor Size</b></p>         | <p>336.4 kcmil Str.</p>   |
| <p><b>VersaCrimp Conductor Range</b></p>                  | <p>#6-#2 Str.</p>   |

|                                     |  |
|-------------------------------------|--|
| <b>VersaCrimp Conductor Minimum</b> | .184 in                                |
| <b>VersaCrimp Conductor Maximum</b> | .292 in                                |
| <b>Dimension D</b>                  | 0.88 in (22 mm)                        |
| <b>Dimension L</b>                  | 1.88 in (48 mm)                        |
| <b>Length before Compression</b>    | 1.88 in (48 mm)                        |
| <b>Compression Method</b>           | VersaCrimp or Conventional Die Tooling |
| <b>Die Size</b>                     | VC6 (all), VC7 (all)                   |
| <b>UL Listed</b>                    | Yes                                    |
| <b>Inhibitor Loaded</b>             | No                                     |
| <b>Color Code</b>                   | Brown                                  |
| <b>Material Type</b>                | Non-Standard                           |
| <b>UPC Code</b>                     | 09635933903                            |
| <b>Standard Package</b>             | 25                                     |
| <b>Standard Package Unit</b>        | Each                                   |
| <b>Min Order Qty</b>                | 25                                     |
| <b>Weight / Ea.</b>                 | 0.627 lbs                              |

### Notes

For use with copper stranded conductor only.

### Features

For use with VersaCrimp or conventional die type tooling.

### Compressed Product Number

VHSS2

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

*All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.*

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.