



[Catalog Home](#)

Product Datasheet

ANDERSON FARGO

VHSS20 -- Versatile Splice



Copper short barrel Versatile splice

Product Specifications

Splice Type



VERSAtile™
Compression Splices
(For use with Die type
and VersaCrimp tools)

Versatile Compression Series



VHSS Series
Compression Splice
VERSAtile™
Minimum Tension
Copper Conductor

PDF Catalog Page

[Click HERE to view the web page.](#)

Conventional Tooling Conductor Size Minimum

0.414 in

Conventional Tooling Conductor Size Maximum

0.419 in

VersaCrimp Conductor Size Minimum

0.232 in

VersaCrimp Conductor Size Maximum

0.419 in

Material

Copper

Conventional Tooling Minimum Conductor

.414 in

Conventional Tooling Maximum Conductor

.419 in

Conventional Tooling Conductor Size

2/0 Str.

VersaCrimp Conductor Range

#4-2/0 Str.

VersaCrimp Conductor Minimum	.232 in
VersaCrimp Conductor Maximum	.419 in
Dimension D	0.94 in (24 mm)
Dimension L	2.00 in (51 mm)
Length before Compression	2.00 in (51 mm)
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	VC6 (all), VC7 (all)
UL Listed	Yes
Inhibitor Loaded	No
Color Code	Black
Material Type	Non-Standard
UPC Code	09635933904
Standard Package	10
Standard Package Unit	Each
Min Order Qty	10
Weight / Ea.	0.098 lbs

Notes

For use with copper stranded conductor only.

Features

For use with VersaCrimp or conventional die type tooling.

Compressed Product Number

VHSS20

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.