

Catalog Home

Product Datasheet ANDERSON FARGO

VHSS500 -- Versatile Splice



Copper short barrel Versatile splice

Product Specification	١S
-----------------------	----

Splice Type



VERSAtile[™]
Compression Splices
(For use with Die type
and VersaCrimp tools)

Versatile Compression Series



VHSS Series Compression Splice VERSAtileTM Minimum Tension Copper Conductor

	Соррег Солицено
PDF Catalog Page	Click HERE to view the web page.
Conventional Tooling Conductor Size Minimum	0.811 in
Conventional Tooling Conductor Size Maximum	0.813 in
VersaCrimp Conductor Size Minimum	0.522 in
VersaCrimp Conductor Size Maximum	0.813 in
Material	Copper
Conventional Tooling Minimum Conductor	.811 in
Conventional Tooling Maximum Conductor	.813 in
Conventional Tooling Conductor Size	500 MCM
VersaCrimp Conductor Range	4/0-500 MCM

VersaCrimp Conductor Minimum	.522 in
VersaCrimp Conductor Maximum	.813 in
Dimension D	1.38 in (35 mm)
Dimension L	2.88 in (73 mm)
Length before Compression	2.88 in (73 mm)
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	VC6FT, VC7FT or VC8
UL Listed	Yes
Inhibitor Loaded	No
Color Code	Brown
Material Type	Non-Standard
UPC Code	09635933911
Standard Package	6
Standard Package Unit	Each
Min Order Qty	6
Weight / Ea.	0.294 lbs

Notes

For use with copper stranded conductor only.

Features

For use with VersaCrimp or conventional die type tooling.

Compressed Product Number

VHSS500

Catalog Home



Warranty Info | **Trademarks** | **Terms of Use**

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.