





UPC Code: 07847732636

Country Of Origin: Mexico

NEMA: Non-NEMA



# **CS8169**

#### **Brand Features**

Leviton Black &White 50Amp Non-NEMA Locking devices are designed for faster wiring and longer life. Made from tough, impact-resistant nylon housings and metal shrouds, these plugs, connectors, receptacles and flanged inlets are designed for rugged environments like construction sites, commercial shipyards and convention centers.

#### Item Description

50Amp, 3-Phase 480V AC, Non-NEMA, 3P, 4W, Black &White Locking Flush Mount Receptacle, Industrial Grade, Grounding, California-Style(CS) - BLACK

#### **Technical Information**

**Electrical Specifications Grounding:** Grounding Amperage: 50 A Voltage: 480 VAC

Pole: 3 Wire: 4

Dielectric Voltage Withstand: 2000V

minimum per UL 498

Maximum Working Voltage: 3-Phase

480V as rated

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30°C temp rise at full-rated current after 150 cycles of

OL at 150% rated DC current

Phase: 3-Phase

**Environmental Specifications** Flammability: Rated V-0 per UL 94 Operating Temperature: -40°C to 75°C

**Environment:** Dry Material Specifications

Face Module: Reinforced Nylon Body & Contract Carrier: Reinforced

Nylon

Shroud: .062inch thick Nickel Plated

Back Cover: Reinforced Nylon Mounting Strap: Single piece SS

Mounting Screws: SS 302/304 Assembly Rivets: SS 302/304

Center Pin: SS 302/304 Connector Contact - Spring: 0.041inch

thick Brass **Connector Contact - Binding Plate:** 

0.100inch thick Brass Contact Rivet: Brass

Box Terminal: 0.062inch thick Copper Terminal Set Screw: SS 302/304

Color: Black

Mechanical Specifications

Terminal ID: X, W, Y, Z and Green for

Terminal Accom.: #10min to #6max AWG Solid or Stranded Wire (Stranded

Wire for Ground only)

Product ID: Ratings and Catalogue No.

molded into face

**Product Features** NEMA: Non-NEMA

Color: Black

Device Type: Locking Receptacle

Brand: Black and White


Standards and Certifications

UL 498: File E13399

CSA C22.2 No. 42: File 152105

**NOM:** 057 RoHS: Compliant

Warranty: Lifetime Limited



### SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

