



Color: White

UPC Code: 07847780638

Country Of Origin: United States

NEMA: L14-30P



2715

Brand Features

Leviton's industry leading locking devices, such as our Black &White line of industrial grade plugs and connectors and our V-0-Max line of industrial grade flush receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

Item Description

30 Amp, 125/250 Volt, NEMA L14-30P, 3P, 4W, Locking Flanged Inlet, Industrial Grade, Grounding - WHITE

Technical Information

AC Horsepower Ratings

At Rated Voltage: 2 HP L-L / 2 HP L-N

Electrical Specifications
Grounding: Grounding
Amperage: 30 A
Voltage: 125/250 VAC

Pole: 3 Wire: 4

Dielectric Voltage: Withstands 2000V

per UL498

Current Limiting: Full Rated Current **Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 60°C

Material Specifications
Face Material: Nylon
Body Material: Nylon
Line Contacts: Solid Brass
Terminal Screws: Brass 10-32
Grounding Screw: Brass 8-32
Strap Material: Thermoplastic Nylon

Color: White

Environment: Dry

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 18-10 AWG **Product ID:** Ratings and NEMA I.D. permanently marked on device

Termination: Back
Product Features
NEMA: L14-30P
Color: White

Device Type: Locking Flanged Inlet

Brand: Black and White Standards and Certifications


NEMA: WD-6 ANSI: C-73


UL498: File E13393

UL Fed Spec WC-596: File E13393 **CSA C22.2 No. 42**: File LR-406

NOM: 057

Warranty: Lifetime Warranty





SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

